

**CP- UNC-TD4K08L3****4K Full HD IR Bullet Camera - 30Mtr.****Main Features**

- 1/2.3" 4K PS CMOS Image Sensor
- 7fps@4K
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 4mm fixed lens
- IR Range of 30 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TD4K08L3

## 4K Full HD IR Bullet Camera - 30Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 S/N Ratio  
 Back Light Compensation  
 Video Compression  
  
 Video Streaming  
  
 Resolution  
 Privacy Mask  
 ICR  
  
 Protocol  
  
 Smart Detection  
 Ethernet  
 User Account  
 IR  
 Smart Phone  
 Operating Temperature  
 Power Source  
 Power Consumption  
 Weatherproof Standard  
 Dimension  
 Weight

### Specification

1/2.3" 4K progressive scan CMOS  
 0.1Lux/F1.6 (Color), 0Lux/F1.6(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 4mm  
 Auto/Manual  
 More than 50dB  
 BLC / HLC / DWDR  
 N/A  
  
 Main Stream: 4K(1~7fps)/3M/1080P/ (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps),  
  
 4K(3840× 2160)3M(2048× 1536)/1080P(1920× 1080) /720P(1280× 720) /D1(704× 576/704× 480) / CIF(352× 288/352× 240)  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
  
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI  
  
 Tripwire, Intrusion, Scene Change, Face detect  
 RJ-45 (10/100Base-T)  
 20 Users  
 IR Range of 30 Mtr.  
 iPhone, iPad, Android, Windows Phone  
 -40°C~+60°C, Less than 95% RH  
 DC12V, PoE (802.3af)  
 Max 7.5W  
 IP66  
 178.4mm × 70mm × 69.9mm  
 528g(683.4g with packaging)