

CP-UVR-3216K8**32 Ch. 720P HDCVI DVR****CP PLUS**
CORAL**Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support Multi-brand network cameras
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-3216K8

32 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode

 Playback

 Backup Mode
 Max User Account
 Record Interval
 Interface Ports
 Ethernet

Specification

Embedded processor
 Embedded LINUX
 1 channel Input, 1 channel Output, BNC
 GUI
 32 channel, BNC
 2 HDMI, 1 VGA, 1TV
 NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
 H.264 / G.711
 1920× 1080, 1280× 1024, 1280× 720, 1024× 768, 800× 600
 Main Stream: 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF / QCIF
 1/4/8/9/16/25/36
 4 rectangular zones (each camera)
 16 channel, BNC
 1 channel, BNC
 Supports
 Supports
 Supports
 16 channel
 6 channel
 8 SATA ports, up to 32TB, 1 eSATA port, up to 16TB
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

 USB Device/eSATA Device/Internal SATA burner/Network
 128 users
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 2 HDMI, 1 VGA, 1 TV, 4 USB2.0, 1 RS485, 1 RS232
 RJ-45 port (10/100M/1000M)

CP- UVR-3216K8

32 Ch. 720P HDCVI DVR



Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP

AC 100~240 V, 50/60 Hz

40W

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 416mm × 68mm

6.5Kg(without HDD)