

AIR-SAP1602E-A-K9 Datasheet

[Get a Quote](#)

Overview

AIR-SAP1602E-A-K9, standalone AP, provides external antenna and A regulatory domain. Cisco 1600 series standalone models with external antennas deliver the IEEE 802.11n performance which sustains up to 300-Mbps data rate.

Quick Specs

Table 1

Product Code	AIR-SAP1602E-A-K9
WiFi Standards	802.11a/b/g/n
Ideal For	Small or midsize enterprises, midmarket
Max Data Rate	300 Mbps
MIMO Radio Design: Spatial Streams	3 x 3:2
Client count/ClientLink client count	128/32
Power	802.3af Ethernet Switch Power Injectors Local Power supply
Antenna	External Antenna
Regulatory Domain	A (A regulatory domain): - 2.412 to 2.462 GHz; 11 channels - 5.180 to 5.320 GHz; 8 channels - 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) - 5.745 to 5.825 GHz; 5 channels
Controller Available	No, standalone mode
Dimensions (W x L x H)	8.7 x 8.7 x 1.84 in.
Package Weight	2.0 kg

The Accessories

Table 2 shows the recommended accessories.

Accessories	Models	Description
Ethernet Switch Power Injectors	AIR-PWRINJ5	Aironet power injector AIR-PWRINJ5, 802.3af, 15.4W
	AIR-PWRINJ4=	Cisco AP power option AIR-PWRINJ4 Power Injector
Local Power supply	AIR-PWR-B	Cisco AP power option PwrSply:100-240VAC,48VDC

Compare to Similar Item

Table 3 shows the comparison between two APs.

Models	AIR-SAP1602E-C-K9	AIR-SAP1602E-A-K9
WiFi Standards	802.11a/b/g/n	802.11a/b/g/n
Antenna	External Antennas	External Antennas
Controller Available	No	No

Regulatory Domain	C (C regulatory domain): - 2.412 to 2.472 GHz; 13 channels - 5.745 to 5.825 GHz; 5 channels	A (A regulatory domain): - 2.412 to 2.462 GHz; 11 channels - 5.180 to 5.320 GHz; 8 channels - 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) - 5.745 to 5.825 GHz; 5 channels
--------------------------	---	--

Get more information

Do you have any question about the AIR-SAP1602E-A-K9? Contact us

now via [Live Chat](#) or sales@gntme.com.

Specification

AIR-SAP1602E-A-K9 Specification	
Product Description	Cisco Catalyst 1600 Series Access Points with External antennas
Devide Type	Wireless Access point
Regulatory domain	A regulatory domain
Software	Cisco Unified Wireless Network Software (available in Q4CY12) Cisco IOS ® Software Release (available in Q4CY12)
Data rates supported	<ul style="list-style-type: none">• 802.11a: up to 54 Mbps• 802.11g: up to 54 Mbps• 802.11n on 2.4 GHz: up to 300Mbps
Maximum number of nonoverlapping channels	5 GHz <ul style="list-style-type: none">• 802.11a:<ul style="list-style-type: none">◦ 20 MHz: 24• 802.11n:<ul style="list-style-type: none">◦ 20 MHz: 24◦ 40 MHz:9 2.4 GHz <ul style="list-style-type: none">• 802.11b/g:<ul style="list-style-type: none">◦ 20 MHz: 3• 802.11n:<ul style="list-style-type: none">◦ 20 MHz: 3
Antenna (purchase separately)	Certified for use with antenna gains up to 6 dBi (2.4 GHz and 5 GHz) Cisco offers the industry's broadest selection of 802.11n antennas delivering optimal coverage for a variety of deployment scenarios
Interfaces	10/100/1000BASE-T autosensing (RJ-45) Management console port (RJ-45)
System memory	256 MB DRAM 32 MB flash
Power consumption (power supply purchase separately)	15.4 Watts (Standard 802.3af POE)
IEEE standards	IEEE 802.11a/b/g, 802.11n, 802.11h, 802.11d
Security	<ul style="list-style-type: none">• 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA• 802.1X• Advanced Encryption Standards (AES), Temporal Key Integrity Protocol (TKIP)

Extensible Authentication Protocol (EAP) types	<ul style="list-style-type: none"> • EAP-Transport Layer Security (TLS) • EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2) • Protected EAP (PEAP) v0 or EAP-MSCHAPv2 • EAP-Flexible Authentication via Secure Tunneling (FAST) • PEAP v1 or EAP-Generic Token Card (GTC) • EAP-Subscriber Identity Module (SIM)
Frequency band and 20-MHz operating channels	A (A regulatory domain): - 2.412 to 2.462 GHz; 11 channels - 5.180 to 5.320 GHz; 8 channels - 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) - 5.745 to 5.825 GHz; 5 channels
Environmental	<ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22 to 158°F (-30 to 70°C) • Nonoperating (storage) Altitude Test: -25°C, 15,000 ft. • Operating temperature: -4 to 122°F (-20 to 50°C) • Operating humidity: 10 to 90 % (noncondensing) • Operating Altitude Test: -40°C, 9843 ft.

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Gntme.com

As a leading network hardware supplier, Gntme.com focuses on original new ICT equipment of **Cisco**, **Huawei**, **HPE**, **Dell**, **Hikvision**, **Juniper**, **Fortinet**, etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

Email:- sales@gntme.com

Contact:- +971 4 2409 998

WhatsApp:- +971503841786

Skype:- [imrank211](#)