

C1-WS3650-24PS/K9 Datasheet

[Get a Quote](#)

Overview

Cisco One Catalyst 3650 24 Port PoE 4x1G Uplink

Specification

C1-WS3650-24PS/K9 Specification

Capacity	
Type	Virtual interfaces (VLANs)
Value	4000
Dimensions & Weight	
Width	17.5 in
Depth	17.6 in
Height	1.7 in
Weight	16.01 lbs
Environmental Parameters	
Min Operating Temperature	23 °F
Max Operating Temperature	113 °F
Humidity Range Operating	5 - 96 % (non-condensing)
Min Storage Temperature	-40 °F
Max Storage Temperature	158 °F
Flash Memory	
Installed Size	2 GB
Header	
Compatibility	PC
Manufacturer	Cisco Systems
Packaged Quantity	1
Product Line	Cisco ONE Catalyst
Model	3650-24PS

CI-WS3650-24PS/K9 Specification

Brand	Cisco
Interface Provided	
Qty	4
Type	Management (mini-USB)
Connector Type	Type B
Comments	Management
PoE Power	30 W
Miscellaneous	
Rack Mounting Kit	Included
Compliant Standards	BSMI CNS 13438 Class A, CISPR 22 Class A, CISPR 24, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, EN 61000-3-2, EN 61000-3-3, EN55022 Class A, EN55024, FCC Part 15 A, GOST, ICES-003 Class A, IEC 60950-1 Second Edition, ISO 7779, KCC, KN22 Class A, KN24, NOM, RoHS, UL 60950-1 Second Edition, VCCI Class A
Authentication Method	RADIUS, Secure Shell (SSH), TACACS+
MTBF	528,280 hours
Height (Rack Units)	1
Color Category	Black
Networking	
Type	Switch
Remote Management Protocol	CLI, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 1, SNMP 2c, SNMP 3, SSH, Telnet
Compliant Standards	IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Status Indicators	Active, PoE, Port duplex mode, Port transmission speed, Status, System
Ports Qty	24
Features	Access Control List (ACL) support, ARP support, DHCP snooping, Dynamic ARP Inspection (DAI), Energy Efficient Ethernet, Flexible NetFlow (FNF), IGMP snooping, Layer 2 switching, Link Aggregation Control Protocol (LACP), MLD snooping, Multiple Spanning Tree Protocol (MSTP) support, Port Aggregation Protocol (PAgP) support, Quality of Service (QoS), RADIUS support, Rapid Per-VLAN Spanning Tree Plus (PVRST+), Rapid Spanning Tree Protocol (RSTP) support, Remote Switch Port Analyzer (RSPAN), Trunking, Uni-Directional Link Detection (UDLD), VLAN support
Routing Protocol	Static IP routing
MAC Address Table Size	32000 entries
Stackable	Stackable
Subcategory	Network hubs and switches

CI-WS3650-24PS/K9 Specification

Power Over Ethernet (PoE)	PoE+
Manageable	Yes
Form Factor	Desktop, Rack-mountable
Jumbo Frame Support	9198 bytes
Subtype	Gigabit Ethernet
PoE Budget	390 W
Performance	
Type	Switching capacity
Value	88 Gbps
Ports	
Qty	24
Type	10/100/1000 (PoE+)
Ports (2nd)	
Qty	4
Type	SFP (mini-GBIC)
Power Device	
Frequency Required	50/60 Hz
Power Provided	640 Watt
Installed Qty	1
Max Supported Qty	2
Nominal Voltage	AC 120/230 V
Power Redundancy	Optional
Power Redundancy Scheme	1 + 1 (with optional power supply)
Type	Internal power supply
Hot-Plug	Hot-plug
RAM	
Installed Size	4 GB
Service	
Support Details Type	Technical support

CI-WS3650-24PS/K9 Specification

Support Details Service Included	Phone consulting
Support Details Full Contract Period	90 days
Service & Support	
Type	Limited lifetime warranty
Service & Support Details	
Response Time	Next business day
Slot Provided	
Type	Stacking Module slot
Total Qty	1
Free Qty	1
Software	
Type	Cisco IOS Universal

Want to Buy

[Order Now](#)[Get a Quote](#)

Why Gntme.com

As a leading network hardware supplier, Gntme.com focuses on original new ICT equipment of **Cisco**, **Huawei**, **HPE**, **Dell**, **Hikvision**, **Juniper**, **Fortinet**, etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

Email:- sales@gntme.com

Contact:- +971 4 2409 998

WhatsApp:- +971503841786

Skype:- [imrank211](https://www.skype.com/people/imrank211)