

## C1-WS3650-48UR/K9 Datasheet

### Overview

[Get a Quote](#)

Cisco ONE Catalyst 3650 48 Port mGig, 8x10G Uplink, LAN Base

### Specification

#### C1-WS3650-48UR/K9 Specification

General	
Device Type	Switch - 48 ports - L3 - managed - stackable
Enclosure Type	Desktop, rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	36 x 10/100/1000 (UPOE) + 12 x 100/1000/2.5G/5G/10G (UPOE) + 8 x 10 Gigabit SFP+ (uplink)
Power Over Ethernet (PoE)	UPOE
PoE Budget	660 W
Performance	Switching capacity: 472 Gbps   Forwarding performance: 351.19 Mpps   Stacking bandwidth: 160 Gbps
Capacity	IPv4 routes: 24000   NetFlow entries: 24000   Virtual interfaces (VLANs): 4094   Switched virtual interfaces (SVIs): 1000
MAC Address Table Size	32000 entries
Jumbo Frame Support	9198 bytes
Routing Protocol	RIP-1, RIP-2, static IP routing, RIPng
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features	Full duplex capability, layer 2 switching, DHCP support, auto-negotiation, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, IPv6 support, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS), RADIUS support, Virtual Route Forwarding-Lite (VRF-Lite), MLD snooping, Dynamic ARP Inspection (DAI), Cisco StackWise Technology, Unicast Reverse Path Forwarding (URPF), Uni-Directional Link Detection (UDLD), Rapid Per-VLAN Spanning Tree Plus (PVRST+), Shaped Round Robin (SRR), LLDP support, Link Aggregation Control Protocol (LACP), MAC Address Notification, Remote Switch Port Analyzer (RSPAN), Hot Standby Router Protocol (HSRP) support, Energy Efficient Ethernet, Strict Priority Queuing (SPQ), Class of Service (CoS), Flexible NetFlow (FNF), DiffServ Code Point (DSCP) support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at
RAM	4 GB
Flash Memory	4 GB
Status Indicators	Port transmission speed, port duplex mode, system, active, status, PoE

## CI-WS3650-48UR/K9 Specification

### Expansion / Connectivity

Interfaces	36 x 1000Base-T RJ-45 UPOE - 60 W ; 1 x USB Type A ; 1 x serial (console) RJ-45 management ; 1 x management (Gigabit LAN) RJ-45 management ; 1 x management (mini-USB) Type B management ; 12 x 100/1000/2.5G/5G/10GBase-T RJ-45 UPOE - 60 W ; 8 x 10GBase-X SFP+
Expansion Slots	1 (total) / 1 (free) x Stacking Module slot

### Power

Power Device	Internal power supply - hot-plug
Installed Qty	1 (installed) / 2 (max)
Power Redundancy	Optional
Power Redundancy Scheme	1 + 1 (with optional power supply)
Power Provided	1100 Watt
Voltage Required	AC 120/230 V (50 - 60 Hz)

### Miscellaneous

Rack Mounting Kit	Included
MTBF	201,680 hours
Compliant Standards	CISPR 22 Class A, GOST, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, NOM, EN 61000-3-3, EN55024, EN55022 Class A, ICES-003 Class A, RoHS, UL 60950-1 Second Edition, KCC, FCC Part 15 A, ISO 7779, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, VCCI Class A, KN24, KN22 Class A

### Software / System Requirements

Software Included	Cisco IOS LAN Base
-------------------	--------------------

### Dimensions & Weight

Width	17.5 in
Depth	19.1 in
Height	1.7 in
Weight	17.81 lbs

### Manufacturer Warranty

Service & Support	Limited warranty - replacement - 5 years - response time: next business day
-------------------	---

### Environmental Parameters

Min Operating Temperature	23 °F
Max Operating Temperature	113 °F

## CI-WS3650-48UR/K9 Specification

Humidity Range Operating	5 - 96 % (non-condensing)
Min Storage Temperature	-40 °F
Max Storage Temperature	158 °F

## Want to Buy

---

[Order Now](#)[Get a Quote](#)

## Why Gntme.com

---

As a leading network hardware supplier, Gntme.com focuses on original new ICT equipment of **Cisco**, **Huawei**, **HPE**, **Dell**, **Hikvision**, **Juniper**, **Fortinet**, etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

---

**Email:-** [sales@gntme.com](mailto:sales@gntme.com)

**Contact:-** +971 4 2409 998

**WhatsApp:-** +971503841786

**Skype:-** [imrank211](#)