

C9115AXE-F Datasheet

[Get Quote](#)



Overview

Cisco Catalyst 9115 Series Wi-Fi 6 Access Points are the next generation of enterprise access points. They are resilient, secure, and intelligent. C9115AXE-H is the Cisco Catalyst 9115AX Series Access Point, Internal antenna; Wi-Fi 6; 4x4:4 MIMO, F Domain.

Product Details

[Cisco AP C9115AXE Series](#) provides these features:

- 802.11ax (Wi-Fi 6)
- Uplink/downlink OFDMA/FDMA
- MU-MIMO technology
- BSS coloring
- Target wake time
- Cisco Mobility Express
- Multigigabit Ethernet support
- Bluetooth 5.0
- Apple Features

Supported Platforms

Table 1 shows the supported platforms and software.

Supported wireless LAN controllers and Software	Recommended Model
Cisco 3500 Series Wireless Controllers	AIR-CT3504-K9
Cisco 5520 Series Wireless Controllers	AIR-CT5520-K9
Cisco 8540 Series Wireless Controllers	AIR-CT8540-K9 AIR-CT8540-1K-K9
Cisco 9800 series Wireless Controllers	C9800-40-K9 C9800-80-K9
Cisco Virtual Wireless Controller	/
Cisco Unified Wireless Network Software Release 8.9 or later	/
Cisco IOS [®] XE Software Release 16.11 or later	/

Compare to Similar Items

Table 2 shows the comparison of Cisco AP 9115AXE Series.

SKU	Description
C9115AXE-A	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, A Domain
C9115AXE-B	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, B Domain
C9115AXE-D	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, D Domain
C9115AXE-E	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, E Domain

C9115AXE-F	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, F Domain
C9115AXE-H	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, H Domain
C9115AXE-I	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, I Domain
C9115AXE-K	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, K Domain
C9115AXE-N	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, N Domain
C9115AXE-Q	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, Q Domain
C9115AXE-S	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, S Domain
C9115AXE-T	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, T Domain
C9115AXE-Z	Cisco Embedded Wireless Controller on Catalyst Access Point; Wi-Fi 6; 4x4:4 MIMO, Z Domain

Get More Information

Do you have any question about the C9115AXE-F?

Contact us now at sales@gntme.com.

Specification

C9115AXE-F Specification	
Description	Cisco Embedded Wireless Controller on Catalyst Access Point, F Domain
Software	<ul style="list-style-type: none"> • Cisco Unified Wireless Network Software Release 8.9 or later • Cisco IOS[®] XE Software Release 16.11 or later
Supported wireless LAN controllers	<ul style="list-style-type: none"> • Cisco Catalyst 9800 Series Wireless Controllers • Cisco 3500, 5520, and 8540 Series Wireless Controllers and Cisco Virtual Wireless Controller
802.11n version 2.0 (and related) capabilities	<ul style="list-style-type: none"> • 4x4 MIMO with four spatial streams • Maximal Ratio Combining (MRC) • 802.11n and 802.11a/g beamforming • 20- and 40-MHz channels • PHY data rates up to 890 Mbps (40 MHz with 5 GHz and 20 MHz with 2.4 GHz) • Packet aggregation: A-MPDU (transmit and receive), A-MSDU (transmit and receive) • 802.11 Dynamic Frequency Selection (DFS) • Cyclic Shift Diversity (CSD) support
802.11ac	<ul style="list-style-type: none"> • 4x4 downlink MU-MIMO with four spatial streams • MRC • 802.11ac beamforming • 20-, 40-, 80-, and 160-MHz channels • PHY data rates up to 3.47 Gbps (160 MHz with 5 GHz) • Packet aggregation: A-MPDU (transmit and receive), A-MSDU (transmit and receive) • 802.11 DFS • CSD support

802.11ax	<ul style="list-style-type: none"> • 4x4 downlink MU-MIMO with four spatial streams • Uplink/downlink OFDMA • TWT • BSS coloring • MRC • 802.11ax beamforming • 20-, 40-, 80-, and 160-MHz channels • PHY data rates up to 5.38 Gbps (160 MHz with 5 GHz and 20 MHz with 2.4 GHz) • Packet aggregation: A-MPDU (transmit and receive), A-MSDU (transmit and receive) • 802.11 DFS • CSD support
Integrated antenna	<ul style="list-style-type: none"> • 2.4 GHz, peak gain 3 dBi, internal antenna, omnidirectional in azimuth • 5 GHz, peak gain 6 dBi, internal antenna, omnidirectional in azimuth
External antenna (sold separately)	<ul style="list-style-type: none"> • Cisco Catalyst 9115AXE Access Points are certified for use with antenna gains up to 6 dBi (2.4 GHz and 5 GHz) • Cisco offers the industry's broadest selection of antennas, delivering optimal coverage for a variety of deployment scenarios
Interfaces	<ul style="list-style-type: none"> • 1x 100, 1000, 2500 Multigigabit Ethernet (RJ-45) – IEEE 802.3bz • Management console port (RJ-45) • USB 2.0 (enabled via future software)
Indicators	<ul style="list-style-type: none"> • Status LED indicates boot loader status, association status, operating status, boot loader warnings, and boot loader errors
Dimensions (W x L x H)	<ul style="list-style-type: none"> • Access point (without mounting brackets): C9115I: 8.0 x 8.0 x 1.5 in. (20.3 x 20.3 x 3.8 cm), C9115E: 8.0 x 8.0 x 1.7 in. (20.3 x 20.3 x 4.3 cm)
Input power requirements	<ul style="list-style-type: none"> • 802.3at Power over Ethernet Plus (PoE+), 802.3bt Cisco Universal PoE (Cisco UPOE+, Cisco UPOE[®]) • Cisco power injector, AIR-PWRINJ6= • 802.3af PoE • Cisco power injector, AIR-PWRINJ5= (Note: This injector supports only 802.3af) <p>Note: When 802.3af PoE is the source of power, both 2.4-GHz and 5-GHz radios will be reduced to 2x2 and Ethernet downgraded to 1 Gigabit Ethernet. In addition, the USB port will be off.</p>
Environmental	<p>Cisco Catalyst 9115AXI</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. • Operating temperature: 32° to 122°F (0° to 50°C) • Operating humidity: 10% to 90% (noncondensing) • Operating altitude test: 40°C, 9843 ft. <p>Note: When the ambient operating temperature exceeds 40 °C, the access point will shift from 4x4 to 2x2 on both the 2.4-GHz and 5-GHz radios, uplink Ethernet will downgrade to 1 Gigabit Ethernet, and the USB interface will be disabled.</p> <p>Cisco Catalyst 9115AXE</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. • Operating temperature: -4° to 122°F (-20° to 50°C) • Operating humidity: 10% to 90% (noncondensing) • Operating altitude test: 40°C, 9843 ft.
System memory	<ul style="list-style-type: none"> • 2048 MB DRAM • 1024 MB flash

<p>Available transmit power settings</p>	<p>2.4 GHz</p> <ul style="list-style-type: none"> • 23 dBm (200mW) • 20 dBm (100mW) • 17 dBm (50mW) • 14 dBm (25mW) • 11 dBm (12.5 mW) • 8 dBm (6.25 mW) • 5 dBm (3.13 mW) • 2 dBm (1.56 mW) • -1 dBm (0.79 mW) • -4 dBm (0.39 mW) <p>5 GHz</p> <ul style="list-style-type: none"> • 26 dBm (400 mW) • 23 dBm (200mW) • 20 dBm (100mW) • 17 dBm (50mW) • 14 dBm (25mW) • 11 dBm (12.5 mW) • 8 dBm (6.25 mW) • 5 dBm (3.13 mW) • 2 dBm (1.56 mW) • -1 dBm (0.79 mW) • -4 dBm (0.39 mW)
<p>Frequency band and 20-MHz operating channels</p>	<p>F regulatory domain:</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 13 channels • 5.250 to 5.350 GHz; 4 channels • 5.725 to 5.825 GHz; 4 channels

Why Gntme.com

As a leading network hardware supplier, Gntme.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), HPE, Dell, Hikvision, Juniper, Fortinet, etc.



200+

Countries we Sold



16,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Mobile: +971 4 2409 998
- Whatsapp: +971503841786
- Email: sales@gntme.com