

# C9404R-48U-BNDL-E Datasheet

[Get a Quote](#)



## Overview

The Cisco Catalyst® 9400 Series switches are Cisco's leading modular enterprise switching access, distribution and core platform built for security, IoT and cloud.

### Quick Specs

Table 1 shows the Quick Specs.

Product Code	C9404R-48U-BNDL-E
Product Description	Catalyst 9400 Series 4 slot, Sup, 1xC9400-LC-48U, DNA-E LIC
Dimensions (H x W x D)	10.47 x 17.30 x 16.30 in. (26.53 x 43.94 x 41.40 cm)
Rack Units (RU)	6RU
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1,C9400-SUP-1XL,C9400-SUP-1XL-Y
ROHS compliance	ROHS5
Rated MTBF (Hours)	2,077,070

### The Accessories

Table 2 shows the recommended elements for the C9404R-48U-BNDL-E.

Items	Models	Descriptions
Modules	C9400-SUP-1=	Cisco Catalyst 9400 Series Supervisor 1 Module Spare
	C9400-SUP-1XL	Cisco Catalyst 9400 Series Supervisor 1XL Module
	C9400-SUP-1XL-Y	Cisco Catalyst 9400 Series Supervisor 1XL-Y with 25G Module
Power supplies supported	C9400-PWR-3200AC	Cisco Catalyst 9400 Series 3200W AC Power Supply
	C9400-PWR-2100AC	Cisco/Cisco Switches/Cisco Switch Catalyst 9400/Cisco Switch Catalyst 9400 Accessories

### Compare to Similar Items

Table 3 shows the comparison.

Product Code	C9407R-96U-BNDL-E	C9404R-48U-BNDL-E
Total number of slots	7	4
Line-card slots	5	2
Supervisor engine slots	2	2
Dedicated supervisor engine slot numbers	3 and 4	2 and 3



Supervisor engine redundancy	Yes	Yes
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y
Maximum PoE per slot	4320W	4320W
Maximum Bandwidth scalability per line- card slot	Up to 480 Gbps on all slots	Up to 480 Gbps on all slots
Number of power supply bays	8	4
AC input power	Yes	Yes
Integrated PoE	Yes	Yes
Power supplies supported	3200W AC, 2100W AC	3200W AC, 2100W AC
Number of fan-tray bays	1	1
Location of 19-inch rack-mount	Front	Front

#### Get More Information

Do you have any question about the Cisco C9404R-48U-BNDL-E?

Contact us now via [sales@gntme.com](mailto:sales@gntme.com).

## Specification

C9404R-48U-BNDL-E Specification	
Product Code	C9404R-48U-BNDL-E
Product Description	Catalyst 9400 Series 4 slot, Sup, 1xC9400-LC-48U , DNA-E LIC
Dimensions (H x W x D)	1.73 x 17.5 x 17.7Inches
Rack Units (RU)	6RU
Total number of slots	4
Line-card slots	2
Supervisor engine slots	2 Note: Slots 2 and 3 are reserved for supervisor engines only in Cisco Catalyst C9404R; slots 1 and 4 are reserved for line cards.
Dedicated supervisor engine slot numbers	2 and 3 Note: Linecards are not supported in the Supervisor slots.
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1,C9400-SUP-1XL,C9400-SUP-1XL-Y
Maximum PoE per slot	4320W Note: Max PoE mentioned is as per the current shipping linecard, however chassis is capable ~4800W PoE per slot.
Maximum Bandwidth scalability per line-card slot	Up to 480 Gbps on all slots Note: 80Gbps per line-card slot when used with C9400-SUP-1 and 240Gbps per line-card slot when used with C9400-SUP-1XL, C9400- SUP-1XL-Y.
Number of power supply bays	4

AC input power	Yes
Integrated PoE	Yes
Power supplies supported	3200W AC, 2100W AC, 3200W DC
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
10/100/1000BASE-T Gigabit (RJ45) ports	96
10/100/1000BASE-T Gigabit Ethernet with POE+ ports	96
Switched 10/100/1000BASE-T Gigabit Ethernet with UPOE ports	96
Switched 10 Gigabit Ethernet ports	48
Cisco Multigigabit Ethernet ports (with UPOE)	48
Switched 1 Gigabit Ethernet ports	96
802.3 BT Type 4 (90W) Ports	96
Environmental conditions	<p>The Cisco Catalyst 9400 Series require the following conditions:</p> <ul style="list-style-type: none"> <li>• Operating temperature</li> <li>• Normal operating* temperature and altitudes: <ul style="list-style-type: none"> <li>-23° to 113°F (-5 to +45°C), up to 6,000 feet (1800 m)</li> <li>-23° to 104°F (-5 to +40°C), up to 10,000 feet (3000 m)</li> </ul> </li> <li>• -*Minimum ambient temperature for cold startup is 0 °C</li> <li>• Short-term** exceptional conditions: <ul style="list-style-type: none"> <li>-23° to 131°F (-5 to +55°C), up to 6,000 feet (1800 m)</li> <li>-23° to 122°F (-5 to +50°C), up to 10,000 feet (3000 m)</li> </ul> </li> <li>• - **Not more than following in one-year period: 96 consecutive hours, or 360 hours total, or 15 occurrences</li> <li>• Storage temperature: -40° to 158°F (-40° to 70°C)</li> <li>• Relative humidity: 10 to 95 percent, noncondensing</li> <li>• Operating altitude: -60 to 3000m</li> </ul>
Regulatory compliance	CE Marking
Safety	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CAN/CSA-C222.2 No. 60950-1</li> <li>• EN 60950-1</li> <li>• IEC 60950-1</li> <li>• AS/NZS 60950.1</li> <li>• IEEE 802.3</li> </ul>
EMC	<ul style="list-style-type: none"> <li>• 47 CFR Part 15</li> <li>• CISPR22 Class A</li> <li>• KN 32 Class A</li> <li>• EN 300 386 V1.6.1</li> <li>• EN 55022 Class A</li> <li>• EN 55032 Class A</li> <li>• CISPR 32 Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• ICES-003 Class A</li> <li>• TCVN 7189 Class A</li> <li>• V-3 Class A</li> <li>• CNS13438 Class A</li> <li>• CISPR24</li> <li>• EN 300 386</li> <li>• EN55024</li> <li>• TCVN 7317</li> <li>• KN35</li> </ul>



Industry EMC, safety, and environmental standards	<ul style="list-style-type: none"><li>• NEBS: Operating temperature: -5 to 55C</li><li>• Relative Humidity: 10-93%</li><li>• Operating Altitude: up to 1829 m (6000 ft) at 55C</li><li>• ETSI 300-019 Requirements are covered under GR-63-CORE with some deviations.</li><li>• SR-3580 NEBS level 3 (GR-63-CORE, to current issue, GR-1089-CORE, to current issue)</li><li>• ETS 300 019-2-1, Class 1.2 Storage</li><li>• ETS 300 019-2-2, Class 2.3 Transportation</li><li>• ETS 300 019-2-3, Class 3.2 Stationary</li><li>• EN50121-4</li><li>• EN 300 386</li></ul>
ROHS compliance	ROHS5
Rated MTBF (Hours)	2,077,070

## Contact Us

**Want to buy this series of products? please contact us:**

- Mobile: +971 4 2409 998
- Whatsapp: +971503841786
- Email: [sales@gntme.com](mailto:sales@gntme.com)

## Order Now

GO to buy this product : <https://gntme.com/c9404r-48u-bndl-e/>