

# C9404R Datasheet

Check its price: [Click Here](#)



## Overview

Cisco Catalyst 9400 Series 4 slot chassis. The Cisco Catalyst® 9400 Series switches are Cisco's leading modular enterprise switching access platform built for security, IoT and cloud. The platform provides unparalleled investment protection with a chassis architecture that is capable of supporting up to 9Tbps of system bandwidth and unmatched power delivery for high density IEEE 802.3BT (60W PoE).

### Quick Specs

Table 1 shows the Quick Specs.

Feature	Cisco Catalyst C9404R
Total number of slots	4
Line-card slots	2
Supervisor engine slots	2
Dedicated supervisor engine slot numbers	2 and 3
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y
Maximum PoE per slot	2880W
Maximum Bandwidth scalability per line-card slot	Up to 480 Gbps on all slots
Number of power supply bays	4
AC input power	Yes
Integrated PoE	Yes
Power supplies supported	3200W AC, 2100W AC
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
Dimensions (H x W x D)	10.47 x 17.30 x 16.30 in. (26.53 x 43.94 x 41.40 cm)
Rack Units (RU)	6 RU
Chassis weight (with fan tray)	39.0 lb (17.2 kg)
Mounting	19-in rack compatible (19-in. rack and cable guide hardware included)

### The Modules, Cards

Table 2 shows the recommended elements for the C9404R.

Model	Description
Modules	
C9400-SUP-1=	Cisco Catalyst 9400 Series Supervisor 1 Module
C9400-SUP-1XL-Y	Cisco Catalyst 9400 Series Supervisor 1XL-Y with 25G Module



C9400-SUP-1XL-Y/2	Cisco Catalyst 9400 Series Redundant Supervisor 1XL-Y with 25G Module
<b>Power Supply</b>	
C9400-PWR-3200AC	Cisco Catalyst 9400 Series 3200W AC Power Supply
C9400-PWR-2100AC	Cisco/Cisco Switches/Cisco Switch Catalyst 9400/Cisco Switch Catalyst 9400 Accessories

## Compare to Similar Items

Table 3 shows the comparison.

Feature	<a href="#">Cisco Catalyst C9404R</a>	Cisco Catalyst C9407R	Cisco Catalyst C9410R
Total number of slots	4	7	10
Line-card slots	2	5	8
Supervisor engine slots	2	2	2
Dedicated supervisor engine slot numbers	2 and 3	3 and 4	5 and 6
Supervisor engine redundancy	Yes	Yes	Yes
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP- 1XL-Y	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP- 1XL-Y	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP- 1XL-Y
Maximum PoE per slot	2880W	2880W	2880W
Maximum Bandwidth scalability per line-card slot	Up to 480 Gbps on all slots	Up to 480 Gbps on all slots	Up to 480 Gbps on all slots
Number of power supply bays	4	8	8
AC input power	Yes	Yes	Yes
Integrated PoE	Yes	Yes	Yes
Power supplies supported	3200W AC, 2100W AC	3200W AC, 2100W AC	3200W AC, 2100W AC

## Get More Information

Do you have any question about the C9404R?

Contact us now via [sales@gntme.com](mailto:sales@gntme.com)

## Specification

Cisco Catalyst C9404R Specification	
Total number of slots	4
Line-card slots	2
Supervisor engine slots	2
Dedicated supervisor engine slot numbers	2 and 3
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y

Maximum PoE per slot	2880W
Maximum Bandwidth scalability per line-card slot	Up to 480 Gbps on all slots
Number of power supply bays	4
AC input power	Yes
Integrated PoE	Yes
Power supplies supported	3200W AC, 2100W AC
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
Dimensions (H x W x D)	10.47 x 17.30 x 16.30 in. (26.53 x 43.94 x 41.40 cm)
Rack Units (RU)	6 RU
Chassis weight (with fan tray)	39.0 lb (17.2 kg)
Mounting	19-in rack compatible (19-in. rack and cable guide hardware included)
Regulatory compliance	CE Marking
Safety	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CAN/CSA-C222.2 No. 60950-1</li> <li>• EN 60950-1</li> <li>• IEC 60950-1</li> <li>• AS/NZS 60950.1</li> <li>• IEEE 802.3</li> </ul>
EMC	<ul style="list-style-type: none"> <li>• 47 CFR Part 15</li> <li>• CISPR22 Class A</li> <li>• KN 32 Class A</li> <li>• EN 300 386 V1.6.1</li> <li>• EN 55022 Class A</li> <li>• EN 55032 Class A</li> <li>• CISPR 32 Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• ICES-003 Class A</li> <li>• TCVN 7189 Class A</li> <li>• V-3 Class A</li> <li>• CNS13438 Class A</li> <li>• CISPR24</li> <li>• EN 300 386</li> <li>• EN55024</li> <li>• TCVN 7317</li> <li>• KN35</li> </ul>
Industry EMC, safety, and environmental standards	<ul style="list-style-type: none"> <li>• NEBS: Operating temperature: -5 to 55C</li> <li>• Relative Humidity: 10-93%</li> <li>• Operating Altitude: up to 1829 m (6000 ft) at 55C</li> <li>• ETSI 300-019 Requirements are covered under GR-63-CORE with some deviations.</li> <li>• SR-3580 NEBS level 3 (GR-63-CORE, to current issue, GR-1089-CORE, to current issue)</li> <li>• ETS 300 019-2-1, Class 1.2 Storage</li> <li>• ETS 300 019-2-2, Class 2.3 Transportation</li> <li>• ETS 300 019-2-3, Class 3.2 Stationary</li> <li>• EN50121-4</li> <li>• EN 300 386</li> </ul>
ROHS compliance	ROHS5



## Contact Us

**Want to buy this series of products? please contact us:**

- Mobile: +971 4 2409 998
- Whatsapp: +971503841786
- Email: [sales@gntme.com](mailto:sales@gntme.com)

## Order Now

GO to buy this product : <https://gntme.com/c9404r-2/>