WS-C3750-48P-AP50



Get a Quote



Overview

3750-48PS + Cisco 4400 Series Wireless LAN Controller bundle provides system wide wireless LAN functions for medium to large-sized facilities. By automating WLAN configuration and management functions, network managers have the control, security, redundancy, and reliability needed to cost-effectively scale and manage their wireless networks as easily as they scale and manage their traditional wired networks. The Cisco 4400 Series Wireless LAN Controller works in conjunction with Cisco Aironet lightweight access points, the Cisco Wireless Control System (WCS), and the Cisco Wireless Location Appliance to support business-critical wireless data, voice, and video applications. It provides real-time communication between lightweight access points and other wireless LAN controllers to deliver centralized security policies, wireless intrusion prevention system (IPS) capabilities, award-winning RF management, quality of service (QoS), and mobility

Specification

| WS-C3750-48P-AP50 data sheet | |
|--------------------------------|--|
| Manufacturer | Cisco Systems, Inc |
| Manufacturer Part Number | WS-C3750-48P-AP50 |
| Product Type | Wireless Controller + Catalyst Switch 48-Port X 2 |
| Height (Rack Units) | 10 |
| Width | 44.3 cm |
| Depth | 40 cm |
| Height | 4.5 cm |
| Bundled with | 2x Cisco Catalyst 3750-48PS |
| Processor / Memory / Storage | |
| Hard Drive | None. |
| Networking | |
| Form Factor | Rack-mountable |
| Ports Qty | 2 |
| Data Link Protocol | Gigabit Ethernet |
| Network / Transport Protocol | TCP/IP, UDP/IP, ICMP/IP, IPSec |
| Remote Management Protocol | SNMP 1, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS |
| Capacity | Manageable access points : 50 |
| LED Status Lights Indicators | Link activity, power, link OK, status, alarm |
| Features | DHCP support, BOOTP support, ARP support, VLAN support, Syslog support, Quality of Service (QoS) |
| Encryption Algorithm | RSA, RC4, MD5, AES, 128-bit WEP, SSL, TLS 1.0, 104-bit WEP, TKIP, WPA, WPA2, PKI, AES-CCMP |
| Compliant Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, X.509 |
| Connectivity / Expansion Slots | |
| Expansion Slots Total (Free) | 1 (1) x Expansion Slot 2 (2) x SFP (mini- GBIC) |

| Interfaces | 1 x management - console - 9 pin D-Sub (DB-9) 1 x management - Ethernet 10Base-T/100Base-TX - RJ-45 |
|-------------------------------------|--|
| Dimensions / Weight / Miscellaneous | |
| Compliant Standards | CE, VCCI, EN 60950, EN55022, ICES-003, EN55024, UL 60950-1 |
| Power Supply Specifications | |
| Power Device | Power supply - hot-plug / redundant - plug-in module |
| Installed Qty | 1 |
| Max Supported Qty | 2 |

Want to Buy

Order Now

Get a Quote

Why gntme.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of <u>Cisco</u>, <u>Huawei, HPE</u>, <u>Dell</u>, <u>Hikvision</u>, <u>Juniper</u>, <u>Fortinet</u>,, etc.











Contact Us

Contact:- +971 4 2409 998
 WhatsApp:- +971503841786
 Skype:- imrank211

• Email: sales@gntme.com