

WS-C6503-E Datasheet

[Get a Quote](#)

Overview

The new 3-slot Cisco Catalyst 6503-E Switch chassis offers a compact 4 rack-unit height and provides centralized network architecture through simplified operations that is ideally suited for multi-Gbps secure data centers, remote access, e-commerce, and converged network solutions. The Cisco Catalyst 6503-E supports Cisco Catalyst 6500 Series end-to-end operational consistency benefits. Any two Cisco Catalyst 6500E series Switches with Supervisor Engine 720-3C/720-3CXL/S2T-10G/S2T-10G-XL can be pooled together into a VSS. The chassis offers superior investment protection by supporting all the Cisco Catalyst 6500 Supervisor Engines and associated LAN, WAN, and services modules.

Quick Specs

Figure 1 shows the appearance of the WS-C6503-E with modules. These modules must be purchased separately.



Table 1 shows the Quick Spec of 6503-E.

Product Code	WS-C6503-E
Number of Slots	3
Supervisor Compatibility	Cisco Catalyst 6500 Series Supervisor Engine 32 Cisco Catalyst 6500 Series Supervisor Engine 720-3B Cisco Catalyst 6500 Series Supervisor Engine 720-3BXL Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3C Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3CXL Cisco Catalyst 6500 Series Supervisor Engine 2T
Power Supply Compatibility * Indicates EoS Power Supply	AC: 1400W, 950W* DC: 950W*
Module Compatibility	All modules based on the software release in the system
With Supervisor Engine 32	12.2(18)SXF
With Supervisor Engine 720	2.2(14)SX
With Supervisor Engine 720-10 GE	12.2(33)SXH
With Supervisor Engine 2T-10 GE	15.0(1)SY

Reliability and Availability Calculated Mean Time Between Failure (MTBF)	860,868
Dimension	7 x 17.37 x 21.75 in (17.8 x 44.1 x 55.2 cm)
Rack Units (RU)	4
Weight	Chassis Only (lbs): 33 Fully Configured (lbs): 85.4

The Accessories

Table 2 shows some accessories of the WS-C6503-E.

Models	Description
WS-SUP720-3BXL	Catalyst 6500/Cisco 7600 WS-SUP720-3BXL Catalyst Supervisor 720 Fabric MSFC3 PFC3BXL
WS-X6716-10G-3C	Catalyst 6500 16 port 10 Gigabit Ethernet w/ DFC3C (req X2)
WS-X6708-10G-3CXL	C6K 8 port 10 Gigabit Ethernet module with DFC3CXL (req. X2)
VS-S2T-10G	Cisco 6500 Supervisor 2T VS-S2T-10G Catalyst 6500 Supervisor 2T - 2 ports 10GbE X2 - 2 ports SFP - MSFC5 PFC4
VS-S2T-10G-XL	Cisco 6500 Supervisor 2T VS-S2T-10G-XL Catalyst 6500 Supervisor 2T 80G System XL
WS-F6700-DFC3B	Catalyst 6500 Dist Fwd Card, 256K Routes for WS-X67xx
SPA-IPSEC-2G	Cisco 7600 / Catalyst 6500 IPsec VPN SPA - DES/3DES/AES
WS-SVC-NAM-1-250S	Cisco Catalyst 6500 and Cisco 7600 Network Analysis Module
SPA-2XOC3-POS	2-port OC3/STM1 POS Shared Port Adapters
SPA-10X1GE	10-port Gigabit Ethernet Shared Port Adapter

Compare to Similar Items

Table 3 shows the comparison of similar items.

Models	WS-C6503-E	WS-C6506-E
Type	Catalyst 6503-E Chassis	Catalyst 6506-E Chassis
Slots	3	6
Supervisor Compatibility	Cisco Catalyst 6500 Series Supervisor Engine 32 Cisco Catalyst 6500 Series Supervisor Engine 720-3B Cisco Catalyst 6500 Series Supervisor Engine 720-3BXL Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3C Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3CXL Cisco Catalyst 6500 Series Supervisor Engine 2T	

Get more information

Do you have any question about the WS-C6503-E?

Contact us now via [Live Chat](#) or sales@gntme.com.

Specification

WS-6503-E Specification

Number of Slots	3
-----------------	---

Supervisor Compatibility	Cisco Catalyst 6500 Series Supervisor Engine 32 Cisco Catalyst 6500 Series Supervisor Engine 720-3B Cisco Catalyst 6500 Series Supervisor Engine 720-3BXL Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3C Cisco Catalyst 6500 Series Supervisor Engine 720-10G-3CXL Cisco Catalyst 6500 Series Supervisor Engine 2T
Power Supply Compatibility * Indicates EoS Power Supply	AC: 1400W, 950W* DC: 950W*
Module Compatibility	All modules based on the software release in the system
With Supervisor Engine 32	12.2(18)SXF
With Supervisor Engine 720	12.2(14)SX
With Supervisor Engine 720-10 GE	12.2(33)SXH
With Supervisor Engine 2T-10 GE	15.0(1)SY
Reliability and Availability Calculated Mean Time Between Failure (MTBF)	860,868
Inches	7 x 17.37 x 21.75
Centimeters	17.8 x 44.1 x 55.2
Rack Units (RU)	4
Chassis Only (lbs)	33
Fully Configured (lbs)	85.4
Input Voltage	100 to 240 VAC -48 to -60 VDC
Safety	UL 60950 Second Edition CAN/CSA-C22.2 No. 60950 Second Edition EN 60950 Second Edition IEC 60950 Second Edition AS/NZS 60950
EMC	FCC Part 15 (CFR 47) Class A VCCI Class A EN55022 Class A CISPR 22 Class A CE marking AS/NZS 3548 Class A ETS300 386 EN55024 EN61000-6-1 EN50082-1
NEBS/ETSI	GR-1089-Core NEBS Level 3 ETS 300 019 Storage Class 1.1 ETS 300 019 Transportation Class 2.3 ETS 300 019 Stationary Use Class 3.1
ATIS Pb free and Energy Efficiency	ATIS-0600020.2010 Pb Free circuit packs ATIS-0600015-2009 General Energy Efficiency Requirements (TEER) ATIS-0600015.03-2009 Switch and Router Energy Efficiency ATIS-0600015.01-2009 Server Energy Efficiency VZ.TPR.9205 Verizon Energy Efficiency Requirements for Telecommunication Equipment (TEEER)
Operating Temperature	32°F to 104°F (0 to 40°C)
Storage Temperature	-4 to 149°F (-20 to 65°C)

Thermal Transition	0.5°C per minute (hot to cold) 33°C per minute (cold to hot)
Relative Humidity	Ambient (noncondensing) operating: 5% to 90% Ambient (noncondensing) nonoperating and storage: 5% to 95%
Operating Altitude	Certified for operation: 0 to 6500 ft (0 to 2000 m) Designed and tested for operation: -200 to 10,000 ft (-60 to 3000 m)

Want to Buy

[Order Now](#)

[Get a Quote](#)

Why Gntme.com

As a leading network hardware supplier, Gntme.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

Email:- sales@gntme.com

Contact:- +971 4 2409 998

WhatsApp:- [+971503841786](https://wa.me/971503841786)

Skype:- [imrank211](https://www.skype.com/user/imrank211)