



# **Cisco Industrial Ethernet 3000**

## **Layer 2/Layer 3 Series Switches Data Sheet**



## Content

Content .....	1
Overview .....	2
Ordering Information .....	21
Where to Buy .....	24
Source .....	24

## Contact Us

- Tel: +971 503823786 / +971 42409998
- Email: [sales@gntme.com](mailto:sales@gntme.com)

## Overview

### Product overview

The Cisco® Industrial Ethernet 3000 Series (IE 3000 Series) is a family of Layer 2 and Layer 3 switches that bring Cisco's leadership in switching to Industrial Ethernet applications with Innovative features, robust security, and superior ease of use. The Cisco IE 3000 Series features:

- Industrial design and compliance
- Tools for easy deployment, management, and replacement
- Network security based on open standards
- Integration of IT and industrial automation networks

The Cisco IE 3000 Series is an ideal product for Industrial Ethernet applications, including factory automation, energy and process control, and Intelligent Transportation Systems (ITSs).

The Cisco IE 3000 offers:

- Design for Industrial Ethernet applications, including extended environmental, shock/vibration, and surge ratings; a complete set of power input options; convection cooling; and DIN-rail or 19" rack mounting
- Support for Power over Ethernet (PoE) up to 15.4W per port
- Support for Power over Ethernet Plus (PoE+) for the PoE+ capable devices up to 30W per port
- Easy setup and management using Cisco DNA™ Center software and the Cisco Device Manager web interface and supporting tools, including Cisco Network Assistant (CNA) and Cisco Prime LMS 4.2
- Easy switch replacement using removable memory, allowing the user to replace a switch without having to reconfigure
- High availability, guaranteed determinism, and reliable security using Cisco IOS® Software
- Recommended software configurations for industrial applications that can be applied at the touch of a button
- Compliance to a wide range of Industrial Ethernet specifications covering industrial automation, ITS, substation, railway, and other markets
- Support for IEEE1588v2, a precision timing protocol with nanosecond-level precision for high-performance applications
- Improved ring resiliency with the support of Resilient Ethernet Protocol (REP)

- Transparent IT integration with the support of Layer 3 routing protocols (IP Services)
- PROFINET v2 certification, with PROFINET conformance class B compliance
- ABB Industrial IT certification

### Configurations

The Cisco IE 3000 Series software, based on Cisco IOS Software, is a rich suite of intelligent services, supporting high availability, Quality of Service (QoS), and security features.



The Cisco IE 3000 Series includes the products listed in Table 1.

**Table 1.** [Cisco IE 3000 Switches](#)

Description	Specification
<a href="#">IE-3000-4TC</a>	<ul style="list-style-type: none"> <li>• 4 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has one active port either 10/100/1000 copper or SFP fiber)</li> <li>• Support up to two expansion modules with various combinations</li> <li>• DC input range 18VDC-60VDC</li> <li>• Layer 2 LAN Base Image</li> </ul>
<a href="#">IE-3000-4TC-E</a>	<ul style="list-style-type: none"> <li>• Same as IE-3000-4TC with Layer 3 IP Services Image</li> </ul>
<a href="#">IE-3000-8TC</a>	<ul style="list-style-type: none"> <li>• 8 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has one active port either 10/100/1000 copper or SFP fiber)</li> <li>• Support up to two expansion modules with various combinations</li> <li>• DC input range 18VDC-60VDC</li> </ul>

	<ul style="list-style-type: none"> <li>● Layer 2 LAN Base Image</li> </ul>
<a href="#">IE-3000-8TC-E</a>	<ul style="list-style-type: none"> <li>● Same as IE-3000-8TC with Layer 3 IP Services Image</li> </ul>
<a href="#">IEM-3000-8TM=</a>	<ul style="list-style-type: none"> <li>● Expansion copper Module for Cisco IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, eight 10/100 TX ports</li> </ul>
<a href="#">IEM-3000-8FM=</a>	<ul style="list-style-type: none"> <li>● Expansion FX Fiber Module for Cisco IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, eight 100 FX ports</li> </ul>
<a href="#">PWR-IE50W-AC=</a>	<ul style="list-style-type: none"> <li>● Expansion Power Module for Cisco IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E and IE-3000-8TC-E switches, supports input AC 100-240V/1.25A or Input DC 125-250V/1A, Output DC 24V/2.1A, DIN-Rail Mount, compatible with PWR-IE3000-AC</li> </ul>
<a href="#">PWR-IE50W-AC-IEC=</a>	<ul style="list-style-type: none"> <li>● Expansion Power Module for Cisco IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E and IE-3000-8TC-E switches, supports Input AC 100-240V/1.25A 50-60Hz, Output DC 24V/2.1A, IEC Plug, DIN-Rail Mount</li> </ul>
<a href="#">IEM-3000-4SM=</a>	<ul style="list-style-type: none"> <li>● Expansion SFP Module for IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, 4 100MB SFP ports</li> <li>● Minimum IOS release 15.0(2)EY</li> </ul>
<a href="#">IEM-3000-8SM=</a>	<ul style="list-style-type: none"> <li>● Expansion SFP Module for IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, 8 100MB SFP ports</li> <li>● Minimum IOS release 15.0(2)EY</li> </ul>
<a href="#">IEM-3000-4PC=</a>	<ul style="list-style-type: none"> <li>● Expansion PoE module for IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, support 4 ports 10/100 PoE/PoE+. External power source is required (44-57 VDC for PoE/50-57 VDC for PoE+)</li> <li>● Minimum IOS release 15.0(2)EY2</li> </ul>
<a href="#">IEM-3000-4PC-4TC=</a>	<ul style="list-style-type: none"> <li>● Expansion PoE module for IE-3000-4TC, IE-3000-8TC, IE-3000-4TC-E, and IE-3000-8TC-E switches, support 4 ports 10/100 PoE/PoE+ and 4 ports non-PoE ports. External power source is required (44-57 VDC for PoE/50-57 VDC for PoE+)</li> </ul>

	<ul style="list-style-type: none"> <li>● Minimum IOS release 15.0(2)EY2</li> </ul>
<a href="#">PWR-IE65W-PC-AC=</a>	<ul style="list-style-type: none"> <li>● AC-DC Power Module for PoE solution, Input AC 100-240V/1.4A, 50-60Hz or Input DC 125-250V/1A. Output 54VDC/1.2 A, DIN-Rail Mount</li> </ul>
<a href="#">PWR-IE65W-PC-DC=</a>	<ul style="list-style-type: none"> <li>● DC-DC Power Module for PoE solution, Input DC 18-60 V/4.3A, Output DC 54V/1.2A, DIN-Rail Mount</li> </ul>

## Industrial Ethernet applications

The new Cisco IE 3000 Series is an ideal product for a variety of Industrial Ethernet applications:

● **Industrial automation:** The Cisco IE 3000 is designed to support a wide array of Industrial Ethernet protocols for automation. The Cisco IE 3000 features a Programmable Logic Controller (PLC) form-factor design with extended environmental ratings, convection cooling, DIN-rail mounting, redundant 24VDC power input, alarm relays, and surge/noise immunity. The Cisco IE 3000 software and configuration tools allow for easy setup, optimized for Industrial Ethernet applications (for example, EtherNet/IP). Multicast control, traffic prioritization, and security features are specified in default templates recommended for these protocols.

● **ITS:** The Cisco IE 3000 supports ITS and other applications for outdoor video and traffic or transportation systems control. The switch supports compliance to NEMA TS-2, a variety of gigabit fiber uplinks, and AC and DC power input options, while Cisco IOS Software supports critical ITS features, including Virtual LAN (VLAN), QoS, Internet Group Management Protocol (IGMP) snooping, and security Access Control Lists (ACLs).

● **Substations:** The Cisco IE 3000 is fully compliant to substation automation specifications, including IEC61850 and IEEE1613. The switch supports high-speed ring recovery; fiber access and uplink ports; AC,DC, and a variety of power input options for the substation environments.

● **Other applications:** The Cisco IE 3000 can be deployed in railway, military, Metro Ethernet, and other applications requiring unique environmental, form factor, or power inputs in harsh environments.

Table 2 gives the features and benefits of the Cisco IE 3000 Series. Table 3 gives the hardware specifications, and Table 4 gives the power specifications. Table 5 gives details on DNA Essentials license support, Table 6 lists supported optics, and Table 7 provides safety and compliance information.

**Table 2.** Features and benefits of Cisco IE 3000 Series

Category	Feature/Benefit
Designed for industrial applications	<ul style="list-style-type: none"> <li>●Extended temperature, vibration, shock and surge, and noise immunity ratings comply to specifications for automation, ITS, and substation environments.</li> <li>● Compact, PLC-style form factor is ideal for deployment in industrial environments.</li> <li>● DIN-rail, wall, and 19" rack mount options allow for deployments in a variety of control systems.</li> <li>●Variety of power input options covers a wide range of power requirements for Industrial Ethernet applications.</li> <li>●Up to 300 deployment configurations, supporting a range of access port densities, copper and fiber uplinks, fiber access ports, and power input, deliver flexibility in deployment.</li> <li>●Support for SFP modules provides uplink connectivity supporting 100BASE-LX, 100BASE-FX, 1000BASE-SX, 1000BASE-LX, and 1000BASE-ZX options.</li> <li>● Alarm relay contacts can be used for an external alert system.</li> </ul>
Ease of deployment, management, and replacement	<p>Cisco DNA™Center enables centralized network management with automation and assurance features. Cisco IE 3000 Series supports DNA Essentials subscription licenses with 3- and 5-year term options.</p> <ul style="list-style-type: none"> <li>●Cisco Express Setup simplifies initial configuration with a web browser, eliminating the need for more complex terminal emulation programs.</li> <li>●Cisco Smartports templates provide the option to apply a default global or interface-level macro with a recommended configuration, allowing the user to easily set up the switch in a configuration optimized for the specific application.</li> <li>●Smartports templates for EtherNet/IP provide an optimized setup for these Industrial Ethernet protocols at the touch of a button.</li> <li>●Swappable Flash memory is ideal for quick and easy switch replacement. Memory can be moved from one switch to another, so a switch can be replaced without the need to reconfigure software features.</li> </ul>

Category	Feature/Benefit
	<ul style="list-style-type: none"> <li>● The Cisco IE 3000 can be managed by PROFINET based management tools. The IE 3000 has PROFINET v2 certification, with PROFINET conformance class B compliance. The IE3000 supports PROFINET QoS on PROFINET default VLAN to prioritize PROFINET real time packets</li> <li>● Simple Network Management Protocol (SNMP) (v1/v2/v3) support allows for management using traditional IT-based management tools, including CiscoWorks.</li> <li>● Device Manager allows web-based switch configurations.</li> <li>● DHCP port-based allocation retains the IP address on a per port basis and simplifies the end-host replacement in an industrial setting.</li> <li>● HTTPS access</li> <li>● Embedded Event Manager (EEM) provides real-time network event detection and on board automation</li> <li>● Cisco Network Assistant (CNA) is a no-charge, Windows-based application that simplifies the administration of networks of up to 250 users. It supports the Cisco IE 3000 and a wide range of Cisco Catalyst® intelligent switches. With CNA, users can manage Cisco Catalyst switches and launch the device managers of Cisco integrated services routers and Cisco Aironet® WLAN access points. Configuration wizards need just a few user inputs to automatically configure the switch to optimally handle different types of traffic: control, voice, video, multicast, and high-priority data.</li> <li>● Cisco Prime LMS support.</li> </ul>
Availability and scalability	<ul style="list-style-type: none"> <li>● Virtual LANs (VLANs) allow for logical segmentation for a network for optimal use of bandwidth.</li> <li>● 802.1q trunking.</li> <li>● QoS classifies and prioritizes data, guaranteeing determinism for mission-critical data.</li> <li>● IGMPv3 snooping provides fast client joins and leaves of multicast streams and limits bandwidth-intensive traffic to only the requestors. An additional querier allows this operation in a Layer 2 only environment.</li> <li>● IGMP filtering provides multicast authentication by filtering out no subscribers and limits the number of concurrent multicast streams available per port.</li> </ul>



Category	Feature/Benefit
	<ul style="list-style-type: none"> <li>● Per-port broadcast, multicast, and unicast storm control prevents faulty end stations from degrading overall systems performance.</li> <li>● IEEE 802.1d Spanning Tree Protocol support for redundant backbone connections and loop-free networks simplifies network configuration and improves fault tolerance.</li> <li>● EtherChannel LACP support for quick recovery and bandwidth utilization.</li> <li>● FlexLinks for fast recovery.</li> <li>● Cisco Hot Standby Router Protocol (HSRP) is supported to create redundant, failsafe routing topologies.</li> <li>● Resilient Ethernet Protocol, scalable up to 130 nodes with a very fast convergence, 50ms.</li> </ul>
Security	<ul style="list-style-type: none"> <li>● IEEE 802.1x with VLAN assignment, guest VLAN, and voice VLAN allows dynamic port-based security, providing user authentication.</li> <li>● Port-based ACLs for Layer 2 interfaces allow application of security policies on individual switch ports.</li> <li>● MAC address filtering prevents the forwarding of any type of packet with a matching MAC address.</li> <li>● Secure Shell (SSH) Protocol v2 and SNMPv3 provide network security by encrypting administrator traffic during Telnet and SNMP sessions. SSHv2 and the cryptographic version of SNMPv3 require a special cryptographic software image because of U.S. export restrictions.</li> <li>● TACACS+ and RADIUS authentication enable centralized control of the switch and restrict unauthorized users from altering the configuration.</li> <li>● MAC address notification allows administrators to be notified of users added to or removed from the network.</li> <li>● Dynamic Host Configuration Protocol (DHCP) snooping allows administrators to help ensure consistent mapping of IP to MAC addresses. This can be used to prevent attacks that attempt to poison the DHCP binding database and to rate limit the amount of DHCP traffic that enters a switch port.</li> <li>● DHCP Interface Tracker (Option 82) augments a host IP address request with the switch port ID.</li> <li>● Port security secures the access to an access or 802.1q trunk port based on MAC address.</li> </ul>

Category	Feature/Benefit
	<ul style="list-style-type: none"> <li>● After a specific time frame, the aging feature removes the MAC address from the switch to allow another device to connect to the same port.</li> <li>●Trusted Boundary provides the ability to trust the QoS priority settings if an IP phone is present and to disable the trust setting if the IP phone is removed, thereby preventing a malicious user from overriding prioritization policies in the network.</li> <li>●Up to 512 ACLs are supported, with two profiles: Security (384 Security ACL entries and 128 QoS policies) and QoS (128 Security ACL entries and 384 QoS policies).</li> <li>●Cisco standard and extended IP security router ACLs define security policies on routed interfaces for control- plane and data-plane traffic.</li> <li>●Dynamic ARP Inspection helps ensure user integrity by preventing malicious users from exploiting the insecure nature of the ARP protocol.</li> <li>●DHCP Snooping prevents malicious users from spoofing a DHCP server and sending out bogus addresses. This feature is used by other primary security features to prevent a number of other attacks such as ARP poisoning.</li> <li>●IP source guard prevents a malicious user from spoofing or taking over another user's IP address by creating a binding table between client's IP and MAC address, port, and VLAN.</li> <li>● Support for private VLANs and SXP (SGT Exchange Protocol).</li> </ul>
<b>High-performance IP routing</b>	<ul style="list-style-type: none"> <li>● Inter-VLAN IP routing for full Layer 3 routing between 2 or more VLANs.</li> <li>●Basic IP unicast routing protocols (static, Routing Information Protocol Version 1 [RIPv1], RIPv2 and RIPv2).</li> <li>●Advanced IP unicast routing protocols (Open Shortest Path First [OSPF], Interior Gateway Routing Protocol [IGRP], Enhanced IGRP [EIGRP], Border Gateway Protocol Version 4 [BGPv4], and Intermediate System-to- Intermediate System [IS-IS]) are supported for load balancing and constructing scalable LANs.</li> <li>●Protocol Independent Multicast (PIM) for IP multicast routing is supported, including PIM Sparse Mode (PIM- SM), PIM Dense Mode (PIM-DM), and PIM sparse-dense mode.</li> </ul>

Category	Feature/Benefit
	<ul style="list-style-type: none"> <li>● Cisco Express Forwarding hardware routing architecture delivers extremely high-performance IP routing.</li> <li>● IPv6 routing (OSPFv6 and EIGRPv6) support in hardware for maximum performance.</li> <li>● Policy-Based Routing (PBR) allows superior control by facilitating flow redirection regardless of the routing protocol configured.</li> <li>● HSRP provides dynamic load balancing and failover for routed links; up to 32 HSRP links supported per unit.</li> <li>● Support for 1000 multicast groups.</li> <li>● VRF-Lite virtualization.</li> </ul>

**Table 3.** Cisco IE 3000 Series switch hardware

Description	Specification
<b>Performance</b>	<ul style="list-style-type: none"> <li>● Wire-speed switching, 16 Gbps switching fabric</li> <li>● Forwarding rate based on 64-byte packets: 6.5 Mpps</li> <li>● 128 MB DRAM</li> <li>● 64 MB Compact Flash memory</li> <li>● Configurable up to 8000 MAC addresses (Layer 2)</li> <li>● Configurable up to 2000 MAC addresses (Layer 3)</li> <li>● Configurable up to 256 IGMP multicast groups (Layer 2)</li> <li>● Configurable up to 1000 IGMP groups and multicast routes (Layer 3)</li> <li>● Configurable up to 3,000 unicast routes (Layer 3)</li> <li>● Support jumbo frames up to 9018 bytes on Gigabit uplink port and mini-jumbo frame (system MTU) up to 1998 bytes on both 10/100 and 10/100/1000 ports</li> </ul>

Description	Specification
Connectors and cabling	<ul style="list-style-type: none"> <li>● 10BASE-T ports: RJ-45 connectors, two-pair Category 3, 4, or 5 Unshielded Twisted-Pair (UTP) cabling</li> <li>● 100BASE-TX ports: RJ-45 connectors, two-pair Category 5 UTP cabling</li> <li>● 1000BASE-T ports: RJ-45 connectors, four-pair Category 5 UTP cabling</li> <li>● 1000BASE-SX, -LX/LH, -ZX SFP-based ports: LC fiber connectors (single/multimode fiber)</li> <li>● 100BASE-LX10, -FX: LC fiber connectors (single/multimode fiber)</li> </ul>
Indicators	<ul style="list-style-type: none"> <li>● Per-port status LED: Link integrity, disabled, activity, speed, full-duplex indications</li> <li>● System-status LED: System, link status, link duplex, link speed, indications</li> </ul>
Dimensions (H x W x D)	<ul style="list-style-type: none"> <li>● Cisco IE-3000-4TC, Cisco IE-3000-4TC-E: 6.0"W x 5.8"H x 4.4"D (152mm W x 147mm H x 112mm D)</li> <li>● Cisco IE-3000-8TC, Cisco IE-3000-8TC-E: 6.0"W x 5.8"H x 4.4"D (152mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-8TM=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-8FM=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-4SM=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-8SM=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-4PC=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco IEM-3000-4PC-4TC=: 3.5"W x 5.8"H x 4.4"D (89mm W x 147mm H x 112mm D)</li> <li>● Cisco PWR-IE50W-AC=: 2.0"W x 5.8"H x 4.4"D (51mm W x 147mm H x 112mm D)</li> <li>● Cisco PWR-IE50W-AC-IEC=: 2.0"W x 5.8"H x 4.4"D (51mm W x 147mm H x 112mm D)</li> <li>● Cisco PWR-IE65W-PC-AC=: 2.6"W x 5.9"H x 4.6"D (66mm W x 150mm H x 117mm D)</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>● Cisco PWR-IE65W-PC-DC=: 2.6"W x 5.9"H x 4.6"D (66mm W x 150mm H x 117mm D)</li> </ul>
Weight	<ul style="list-style-type: none"> <li>● Cisco IE-3000-4TC, Cisco IE-3000-4TC-E: 4.4 lb (2.0 kg)</li> <li>● Cisco IE-3000-8TC, Cisco IE-3000-8TC-E: 4.4 lb (2.0 kg)</li> <li>● Cisco IEM-3000-8TM=: 2.2 lb (1.0 kg)</li> <li>● Cisco IEM-3000-8FM=: 3.2 lb (1.45 kg)</li> <li>● Cisco IEM-3000-4SM=: 2.5 lb (1.1 Kg)</li> <li>● Cisco IEM-3000-8SM=: 3.0 lb (1.38 Kg)</li> <li>● Cisco IEM-3000-4PC=: 2.4 (1.08 Kg)</li> <li>● Cisco IEM-3000-4PC-4TC=: 2.5 (1.16 Kg)</li> <li>● Cisco PWR-IE50W-AC=: 1.4 lb (0.65 kg)</li> <li>● Cisco PWR-IE50W-AC-IEC=: 1.4 lb (0.65kg)</li> <li>● Cisco PWR-IE65W-PC-DC=: 2.6 (1.18 Kg)</li> <li>● Cisco PWR-IE65W-PC-AC=: 2.7 (1.24 Kg)</li> </ul>
Operating environment	<p>Operating temperature: -40C to +75C</p> <ul style="list-style-type: none"> <li>● -40C to +70C (Vented Enclosure – 40 LFM Air Flow)</li> <li>● -40C to +60C (Sealed Enclosure – 0 LFM Air Flow)</li> <li>● -24C to +75C (Fan or Blower equipped Enclosure – 200 LFM Air Flow)</li> <li>● -40C to +85C (IEC 60068-2-2 Environmental Type Testing – 16 hours)</li> <li>● Storage temperature: -40C to +85C</li> <li>● Operating relative humidity: 10 to 95% (non-condensing)</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• Operating altitude: Up to 13,000 ft (3963m)</li> <li>• Storage altitude: Up to 15,000 ft (4573m)</li> </ul>
Mean Time Between Failures (MTBF)	<ul style="list-style-type: none"> <li>• Cisco IE-3000-4TC, Cisco IE-3000-4TC-E: 363,942</li> <li>• Cisco IE-3000-8TC, Cisco IE-3000-8TC-E: 329,451</li> <li>• Cisco IEM-3000-8TM=: 926,999</li> <li>• Cisco IEM-3000-8FM=: 264,689</li> <li>• Cisco IEM-3000-4SM=: 8,887,990</li> <li>• Cisco IEM-3000-8SM=: 7,732,890</li> <li>• Cisco IEM-3000-4PC=: 1,494,990</li> <li>• Cisco IEM-3000-4PC-4TC=: 1,291,440</li> <li>• Cisco PWR-IE50W-AC=: 1,662,359</li> <li>• Cisco PWR-IE50W-AC-IEC=: 1,662,359</li> <li>• Cisco PWR-IE65W-PC-DC=: 2,468,430</li> <li>• Cisco PWR-IE65W-PC-AC=: 2,488,401</li> </ul>

**Table 4.** Power specifications for Cisco IE 3000 Series switches

Description	Specification
Maximum power consumption	<ul style="list-style-type: none"> <li>• Cisco IE-3000-4TC, Cisco IE-3000-4TC-E: 15.1W</li> <li>• Cisco IE-3000-8TC, Cisco IE-3000-8TC-E: 15.7W</li> <li>• Cisco IEM-3000-8TM=: 2.8W</li> <li>• Cisco IEM-3000-8FM=: 10.1W</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• Cisco IEM-3000-4SM=: 7.6W</li> <li>• Cisco IEM-3000-8SM=: 12.2W</li> <li>• Cisco IEM-3000-4PC=: 7.3W</li> <li>• Cisco IEM-3000-4PC-4TC=: 7.9W</li> </ul>
Input voltage and currents supported	<ul style="list-style-type: none"> <li>• Cisco IE-3000-4TC, Cisco IE-3000-8TC, 18-60VDC</li> <li>• Cisco IEM-3000-4PC=, IEM-3000-4PC-4TC=: 44-57V input</li> <li>• Cisco PWR-IE50W-AC=: 100-240VAC/1.25A or 125-250VDC/1A</li> <li>• Cisco PWR-IE50W-AC-IEC=: 100-240VAC/1.25A, 50-60Hz</li> <li>• Cisco PWR-IE65W-PC-DC=: 18-60VDC/4.3A</li> <li>• Cisco PWR-IE65W-PC-AC=: 100-240VAC/1.4A or 125-250V/1A</li> </ul>
Power rating	<ul style="list-style-type: none"> <li>• Cisco IE-3000-4TC, Cisco IE-3000-4TC-E: .05KVA</li> <li>• Cisco IE-3000-8TC, Cisco IE-3000-8TC-E: .05KVA</li> </ul>

**Table 5.** Cisco IE 3000 DNA Essentials

Feature	Description
Cisco DNA Center	Discovery, topology, inventory, software image management
Visibility	DNA assurance, Device 360
Day-zero network bring-up automation	Cisco Network Plug-and-Play application

**Table 6.** SFP transceivers support for Cisco IE 3000 Series switches

Part number	Specification	SFP type	Max distance	Cable type	Temp range	DOM support
<a href="#">GLC-FE-100FX-RGD</a>	100BASE-FX	FE	2km	MMF	IND	Yes
<a href="#">GLC-FE-100LX-RGD</a>	100BASE-LX10	FE	10km	SMF	IND	Yes
<a href="#">GLC-FE-T-I=</a>	100BASE-T	FE	100m	Copper	IND	NA
<a href="#">GLC-FE-100FX</a>	100BASE-FX	FE	2km	MMF	COM	No
<a href="#">GLC-FE-100LX</a>	100BASE-LX10	FE	10km	SMF	COM	No
<a href="#">GLC-FE-100EX</a>	100BASE-EX	FE	40km	SMF	COM	No
<a href="#">GLC-FE-100ZX</a>	100BASE-ZX	FE	80km	SMF	COM	No
<a href="#">GLC-FE-100BX-D</a>	100BASE-BX10	FE	10km	SMF	COM	No
<a href="#">GLC-FE-100BX-U</a>	100BASE-BX10	FE	10km	SMF	COM	Yes
<a href="#">GLC-SX-MM-RGD</a>	1000BASE-SX	GE	550m	MMF	IND	Yes
<a href="#">GLC-LX-SM-RGD</a>	1000BASE-LX/LH	GE	550m/10km	MMF/SMF	IND	Yes
<a href="#">GLC-ZX-SM-RGD</a>	1000BASE-ZX	GE	70km	SMF	IND	Yes
<a href="#">GLC-BX40-U-I</a>	1000BASE-BX40	GE	40km	SMF	IND	Yes
<a href="#">GLC-BX40-D-I</a>	1000BASE-BX40	GE	40km	SMF	IND	Yes
<a href="#">GLC-BX40-DA-I</a>	1000BASE-BX40	GE	40km	SMF	IND	Yes
<a href="#">GLC-BX80-U-I</a>	1000BASE-BX80	GE	80km	SMF	IND	Yes



Part number	Specification	SFP type	Max distance	Cable type	Temp range	DOM support
<a href="#">GLC-BX80-D-I</a>	1000BASE-BX80	GE	80km	SMF	IND	Yes
<a href="#">GLC-SX-MMD</a>	1000BASE-SX	GE	550m	MMF	EXT	Yes
<a href="#">GLC-LH-SMD</a>	1000BASE-LX/LH	GE	550m/10km	MMF/SMF	EXT	Yes
<a href="#">GLC-EX-SMD</a>	1000BASE-EX	GE	40km	SMF	EXT	Yes
<a href="#">GLC-ZX-SMD</a>	1000BASE-ZX	GE	70km	SMF	EXT	Yes
<a href="#">GLC-BX-D</a>	1000BASE-BX10	GE	10km	SMF	COM	Yes
<a href="#">GLC-BX-U</a>	1000BASE-BX10	GE	10km	SMF	COM	Yes
CWDM-SFP-xxxx= (8 freq)	CWDM 1000BASE-X	GE		SMF	COM	Yes
DWDM-SFP-xxxx= (40 freq)	DWDM 1000BASE-X	GE		SMF	COM	Yes
<a href="#">SFP-GE-S</a>	1000BASE-SX	GE	550m	MMF	EXT	Yes
<a href="#">SFP-GE-L</a>	1000BASE-LX/LH	GE	550m/10km	MMF/SMF	EXT	Yes
<a href="#">SFP-GE-Z</a>	1000BASE-ZX	GE	70km	SMF	EXT	Yes
<a href="#">GLC-SX-MM</a>	1000BASE-SX	GE	550m	MMF	COM	No
<a href="#">GLC-LH-SM</a>	1000BASE-LX/LH	GE	550m/10km	MMF/SMF	COM	No
<a href="#">GLC-ZX-SM</a>	1000BASE-ZX	GE	70km	SMF	COM	Yes
<a href="#">GLC-TE</a>	1000BASE-T	GE	100m	Copper	EXT	NA
<a href="#">GLC-T</a>	1000BASE-T	GE	100m	Copper	COM	NA

Part number	Specification	SFP type	Max distance	Cable type	Temp range	DOM support
GLC-T-RGD=	1000BASE-T	GE	100m	Copper	IND	NA

**Table 7.** Compliance specifications

Description	Specification
<b>Standard safety certifications</b>	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CSA C22.2 No. 60950-1</li> <li>• TUV/GS to EN 60950-1</li> <li>• CB to IEC 60950-1 with all country deviations</li> <li>• NOM</li> </ul>
<b>Mechanical stability</b>	<ul style="list-style-type: none"> <li>• IEC 60628-2-27 Shock 20g (operational), 30g (nonoperational)</li> </ul>
<b>Electromagnetic emissions</b>	<ul style="list-style-type: none"> <li>• FCC Part 15 Class A</li> <li>• EN 55022</li> <li>• CISPR22</li> <li>• CISPR11</li> <li>• VCCI Class A</li> <li>• AS/NZS 3548 Class A</li> <li>• CNS 13438 Class A</li> <li>• KN 22 Class A</li> </ul>
<b>Electromagnetic immunity</b>	<ul style="list-style-type: none"> <li>• EN 55024</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• AS/NZS CISPR 24</li> <li>• KN 24</li> <li>• IEC/EN 61000-4-2 (Electro Static Discharge)</li> <li>• IEC/EN 61000-4-3 (Radiated Immunity)</li> <li>• IEC/EN 61000-4-4 (Fast Transients)</li> <li>• IEC/EN 61000-4-5 (Surge)</li> <li>• IEC/EN 61000-4-6 (Conducted Immunity)</li> <li>• IEC/EN 61000-4-8 (Power Frequency Magnetic Field Immunity)</li> <li>• IEC/EN 61000-4-9 (Pulse Magnetic Field Immunity)</li> <li>• IEC/EN 61000-4-10 (Oscillatory Magnetic Field Immunity)</li> <li>• IEC/EN 61000-4-11 (AC power Voltage Immunity)</li> <li>• IEC/EN 61000-4-16 (Low Frequency Conducted CM Disturbances)</li> <li>• IEC/EN 61000-4-17 (Ripple on DC Input Power)</li> <li>• IEC/EN 61000-4-18 (Damped Oscillatory Wave)</li> <li>• IEC/EN 61000-4-29 (Voltage Dips Immunity, DC power)</li> <li>• IEEE C37.90 (Surge)</li> <li>• IEEE C37.90.1 (Fast Transients)</li> <li>• IEEE C37.90.2 (Radiated Immunity)</li> <li>• IEEE C37.90.3 (Electro Static Discharge)</li> </ul>
Industry specifications	<ul style="list-style-type: none"> <li>• EN 61131-2 Programmable Controllers (EMC/EMI, environmental, mechanical)</li> <li>• IEEE 1613 Power Station and Substation Networking Devices</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• IEC 61850-3 Power Station and Substation Communication Networks and Systems</li> <li>• EN 61326-1 Electrical Equipment for Measurement, Control and Laboratory Use - EMC</li> <li>• EN 61000-6-1 Immunity for Light Industrial Environments</li> <li>• EN 61000-6-2 Immunity for Industrial Environments</li> <li>• EN 61000-6-4 Emissions for Industrial Environments</li> <li>• TS 61000-6-5 EMC Immunity for Power Station and Substation</li> <li>• EN 50155 Railway, Electronic Equipment on Rolling Stock (EMI/EMC, environmental, mechanical)</li> <li>• EN 50121-3-2 Railway, Electromagnetic Compatibility on Rolling Stock</li> <li>• EN 50121-4 Railway, Emission and Immunity of Signaling and Telecommunications Apparatus</li> <li>• EN 60945 Maritime Navigation and Radio-communication Equipment and Systems</li> <li>• IEC 60533 Shipboard Electrical and Electronic Installation EMC</li> <li>• Marine Type Approval (BV, DNV, Korean Register, Lloyd Register)</li> <li>• NEMA TS-2 (EMC, environmental, mechanical)</li> <li>• ABB Industrial IT certification</li> <li>• ODVA Industrial EtherNet/IP support</li> <li>• PROFINETv2 support</li> <li>• Directive 2011/65/EU RoHS</li> <li>• IP20</li> </ul>
<b>Hazardous locations</b>	<ul style="list-style-type: none"> <li>• UL/CSA 60079-0, -15 (Class 1, Div 2 A-D) (requires cabinet enclosure)</li> <li>• EN 60079-0, -15 ATEX Certification (Class 1, Zone 2 A-D) (requires cabinet enclosure)</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• IEC 60079-0, -15 (Test report only) (requires cabinet enclosure)</li> <li>• UL 508</li> <li>• CSA C22.2 No. 142</li> </ul>
Compliance marking	<ul style="list-style-type: none"> <li>• UL/CSA</li> <li>• CE (Europe)</li> <li>• C-Tick (Australia/New Zealand)</li> <li>• KCC (Korea)</li> <li>• ANATEL (Brazil)</li> <li>• China RoHS</li> </ul>
Operating temperature	<ul style="list-style-type: none"> <li>• -40 C to +70 C (vented enclosure operating)</li> <li>• -40 C to +60 C (sealed enclosure operating)</li> <li>• -34 C to +75 C (fan or blower-equipped enclosure operating)</li> <li>• -40 C to +85 C (IEC Environmental Type Testing, 16 hours)</li> <li>• Operational altitude: Up to 13,000 ft</li> </ul>
Storage temperature	<ul style="list-style-type: none"> <li>• -40 C to +85 C (storage temperature)</li> <li>• Storage altitude: Up to 15,000 ft</li> </ul>
Humidity	<ul style="list-style-type: none"> <li>• Relative humidity: 5% to 95% non-condensing</li> </ul>
Telco	<ul style="list-style-type: none"> <li>• Common Language Equipment Identifier (CLEI) code</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>• Five year limited warranty</li> </ul>

## Ordering Information

Table 9 gives ordering information for the Cisco IE 3000 Series.

**Table 9.** Ordering Information for Cisco IE 3000 Series

Model	Specification
<a href="#">IE-3000-4TC</a>	<ul style="list-style-type: none"> <li>• Industrial Ethernet switch</li> <li>• 4 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has 1 10/100/1000 Ethernet port and 1 SFP-based Gigabit Ethernet port, 1 port active)</li> <li>• Each switch supports 2 Cisco modules, 1 Cisco IEM-3000-8FM= module, or 1 Cisco IEM-3000-8TM= module and 1 Cisco IEM-3000-8FM= module</li> <li>• Layer 2 LAN Base image installed</li> </ul>
<a href="#">IE-3000-8TC</a>	<ul style="list-style-type: none"> <li>• Industrial Ethernet switch</li> <li>• 8 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has 1 10/100/1000 Ethernet port and 1 SFP-based Gigabit Ethernet port, 1 port active)</li> <li>• Each switch supports 2 Cisco IEM-3000-8TM= modules, 1 Cisco IEM-3000-8FM= module, or 1 Cisco IEM-3000-8TM= module and 1 Cisco IEM-3000-8FM= module</li> <li>• Layer 2 LAN Base image installed</li> </ul>
<a href="#">IE-3000-4TC-E</a>	<ul style="list-style-type: none"> <li>• Industrial Ethernet switch</li> <li>• 4 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has 1 10/100/1000 Ethernet port and 1 SFP-based Gigabit Ethernet port, 1 port active)</li> <li>• Each switch supports 2 Cisco modules, 1 Cisco IEM-3000-8FM= module, or 1 Cisco IEM-3000-8TM= module and 1 Cisco IEM-3000-8FM= module</li> <li>• Layer 3 IP Services image installed</li> </ul>
<a href="#">IE-3000-8TC-E</a>	<ul style="list-style-type: none"> <li>• Industrial Ethernet switch</li> </ul>

Model	Specification
	<ul style="list-style-type: none"> <li>• 8 Ethernet 10/100 ports and 2 dual-purpose uplinks (each dual-purpose uplink port has 1 10/100/1000 Ethernet port and 1 SFP-based Gigabit Ethernet port, 1 port active)</li> <li>• Each switch supports 2 Cisco IEM-3000-8TM= modules, 1 Cisco IEM-3000-8FM= module, or 1 Cisco IEM-3000-8TM= module and 1 Cisco IEM-3000-8FM= module</li> <li>• Layer 3 IP Services image installed</li> </ul>
<a href="#"><u>IEM-3000-8TM=</u></a>	<ul style="list-style-type: none"> <li>• Expansion Copper module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 8 10/100 TX ports</li> </ul>
<a href="#"><u>IEM-3000-8FM=</u></a>	<ul style="list-style-type: none"> <li>• Expansion Fiber module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 8 100 FX ports</li> </ul>
<a href="#"><u>IEM-3000-4SM=</u></a>	<ul style="list-style-type: none"> <li>• Expansion SFP module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 4 100M SFP ports</li> </ul>
<a href="#"><u>IEM-3000-8SM=</u></a>	<ul style="list-style-type: none"> <li>• Expansion SFP module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 8 100M SFP ports</li> </ul>
<a href="#"><u>IEM-3000-4PC=</u></a>	<ul style="list-style-type: none"> <li>• Expansion PoE/PoE+ module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 4 10/100 PoE/PoE+ ports</li> <li>• External PoE power source (44-57 VDC for PoE/50-57 VDC for PoE+)</li> </ul>
<a href="#"><u>IEM-3000-4PC-4TC=</u></a>	<ul style="list-style-type: none"> <li>• Expansion PoE/PoE+ module for Cisco IE-3000-4TC and IE-3000-8TC switches</li> <li>• 4 non-PoE ports and 4 10/100 PoE/PoE+ ports</li> <li>• External PoE power source (44-57 VDC for PoE/50-57 VDC for PoE+)</li> </ul>
<a href="#"><u>PWR-IE50W-AC=</u></a>	<ul style="list-style-type: none"> <li>• Expansion power module for IE-3000-4TC and IE-3000-8TC switches</li> </ul>

Model	Specification
<a href="#">PWR-IE50W-AC-IEC=</a>	<ul style="list-style-type: none"> <li>• Expansion power module for IE-3000-4TC and IE-3000-8TC switches</li> </ul>
<a href="#">PWR-IE65W-PC-AC=</a>	<ul style="list-style-type: none"> <li>• AC-DC, 54VDC power module to support 65 watts for PoE/PoE+ modules</li> </ul>
<a href="#">PWR-IE65W-PC-DC=</a>	<ul style="list-style-type: none"> <li>• DC-DC, 54VDC power module to support 65 watts for PoE/PoE+ modules</li> </ul>
<a href="#">CAB-SM-LCSC-1M</a>	<ul style="list-style-type: none"> <li>• 1m-fiber single-mode LC-to-SC connectors</li> </ul>
<a href="#">CAB-SM-LCSC-5M</a>	<ul style="list-style-type: none"> <li>• 5m-fiber single-mode LC-to-SC connectors</li> </ul>
<a href="#">CF-IE3000=</a>	<ul style="list-style-type: none"> <li>• IE 3000 Compact Flash</li> </ul>
<a href="#">PWR-IE3000-CLP=</a>	<ul style="list-style-type: none"> <li>• IE 3000 Power Transformer Spare connector clip</li> </ul>
<a href="#">PWR-IE3000-CNCT=</a>	<ul style="list-style-type: none"> <li>• IE 3000 Power Spare connector</li> </ul>
<a href="#">LPNL-IE3000=</a>	<ul style="list-style-type: none"> <li>• IE 3000 Left Panel Spare</li> </ul>
<a href="#">RPNL-IE3000=</a>	<ul style="list-style-type: none"> <li>• IE 3000 Right Panel Spare</li> </ul>
<a href="#">DINCLP-IE3000=</a>	<ul style="list-style-type: none"> <li>• Din-rail clip 4 pack Spare</li> </ul>
<a href="#">BMP-IE3000=</a>	<ul style="list-style-type: none"> <li>• Din-rail clip bumper 4 pack Spare</li> </ul>
<a href="#">STK-RACKMNT-2955=</a>	<ul style="list-style-type: none"> <li>• Din-rail adapter for rack mounting</li> </ul>
<a href="#">IE-SW-SPARE</a>	<ul style="list-style-type: none"> <li>• Spare IOS software upgrade part number (L2 to L3 features)</li> </ul>
<a href="#">IE3000-DNA-E-L</a>	<ul style="list-style-type: none"> <li>• DNA Essentials license</li> </ul>
<a href="#">IE3000-DNA-E-L-3Y</a>	<ul style="list-style-type: none"> <li>• DNA Essentials 3-year term license option</li> </ul>
<a href="#">IE3000-DNA-E-L-5Y</a>	<ul style="list-style-type: none"> <li>• DNA Essentials 5-year term license option</li> </ul>



## Where to Buy

Want to buy this series of products? please contact:

- Tel: +971 503823786 / +971 42409998
- Email: [sales@gntme.com](mailto:sales@gntme.com)

### About us

We provide the products to the local as well as international markets. This also involves **import, export, and re-export** of electronic and electrical appliances, computer and networking equipment and software. We are keen on providing a complete set of IT Solutions for every small business to the corporate-level business.

## Source

<https://gntme.com/>