



Overview

IE-2000-4T-B is the IE2000 series IE 4 10/100, 2 FE, and LAN Base switch. The Cisco IE 2000 Series are designed for low cost, low ports, and small sizes. They offer:

- 1.Four, eight, or 16 10/100Base-T Ethernet ports (Small Form-Factor Pluggable [SFP] downlinks on selected models); fixed configurations with a compact form factor
- 2. Two gigabit combo ports: SFP (100 Mbps and 1 Gbps) or RJ45 uplink
- 3. Dual-input DC power supply, alarm relays, DIN rail mount
- 4. Industrial Power over Ethernet (PoE) solution
- 5. Conformal coating available
- 6. Swappable SD flash card and mini-USB connector
- 7. Industrial environmental compliance and certifications
- 8. Industrial partner applications: Ethernet/IP and PROFINET

Quick Spec

Table 1 shows the quick spec.

Part Number	IE-2000-4T-B
Total Ports	6
RJ45 ports	6 FE
Manufacturing license	LAN Base
Dimensions (H x W x D) including DIN rail	5.1" H x 2.95" W x 4.51" D in (130mm H x 74.9mm W x 115mm D)
Weight	IE-2000 6 ports chassis: 2.45 lb (1.11 kg)

Supported Products

Table 2 shows the supported modules, cards, licenses and accessories.

Model	Description
SD-IE-1GB	1GB SD Memory Card
L-IE2000-L-B=	IE2000 LAN Lite to LAN Base e-license
LIC-IE2000-L-IP=	IE2000 LAN Lite to IPLite e-license
STK-RACK-DINRAIL=	19 in. DIN Rail mount kit

Compare to Similar Items

Table 3 shows the comparison.

Part Number	IE-2000-4TS-B	IE-2000-4T-B	IE-2000-4TS-G-B
Total Ports	6	6	6
RJ45 ports	4 FE	6 FE	4 FE
SFP ports	2 FE	-	2 GE

Manufacturing license LAN Base LAN Base

Datasheet Download

[PDF] Cisco Industrial Ethernet 2000 Series Switches Data Sheet

Ordering Guide

[PDF] Cisco Industrial Ethernet Switches Ordering Guide

[PDF] Simple Cisco Industrial Ethernet Switches (IE 4000, IE 2000 included) Selection Guides

Get more information

Do you have any question about the C9500-32QC-A? Contact us now via **Live Chat** or sales@gntme.com

Specification

	IE-2000-4T-B Specification			
Physical Specification				
Total Ports	6			
RJ45 ports	6 FE			
Manufacturing license	LAN Base			
Hardware	 256 MB DRAM with ECC memory IEEE 1588v2 FPGA 64 MB on-board flash memory 1GB removable SD flash memory card (optional) Mini-USB connector 			
Alarm	Alarm I/O: Two alarm inputs to detect dry contact open or close; one alarm output relay			
Power consumption	4-port downlink models: 9.5-15 W			
Connectors and cabling	• 10/100/1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling			
Dimensions (H x W x D) including DIN rail	• IE-2000 6 ports (copper downlinks) chassis: 5.1"H x 2.95"W x 4.51"D in (130mm H x 74.9mm W x 115mm D)			
Weight	IE-2000 6 ports chassis: 2.45 lb (1.11 kg)			
IE2000 Software F	eatures			
LAN Lite license	Baseline features			
Layer 2 switching	IEEE 802.1, 802.3, 802.3at, 802.3af standard (see Table 8), VTPv2, NTP, UDLD, CDP, LLDP, Unicast MAC filter, Resilient Ethernet Protocol (REP), Media Redundancy Protocol (MRP) Ring (IEC 62439-2)			
Security	SCP, SSH, SNMPv3, TACACS+, RADIUS Server/Client, MAC Address Notification, BPDU Guard, SPAN session			
Multicast	IGMPv1, v2, v3 Snooping, IGMP filtering, IGMP Querier			
Management	Fast Boot, Express Setup, Web Device Manager, CNA, Cisco Prime, LMS, MIB, SmartPort, SNMP, syslog			
Industrial Ethernet	EtherNet/IP, Profinet v2			
LAN Base license	Additional features			

Layer 2 switching	VTPv3, EtherChannel, Voice VLAN, Flexlink
Security	IPv4 Port-Security, DHCP Snooping, Dynamic ARP Inspection, IP Source Guard, 802.1x, Guest VLAN. MAC Authentication Bypass, 802.1x Multi-Domain Authentication, Storm Control, Trust Boundary, Access-List (ACL)
Quality of service	IPv4 Ingress Policing, Rate-Limit, Egress Queuing/Shaping, AutoQoS, PROFINET QoS
Management	Port-Based DHCP, Storm Control - Unicast, Multicast, Broadcast, SPAN Sessions, RSPAN, DHCP Server, Customized TCAM/SDM Size Configuration, Embedded Event Manager (EEM)
Industrial Ethernet	IEEE 1588 PTPv2
IPv4 routing	IPv4 static routing
IPv6 routing	IPv6 host support, HTTP over IPv6, SNMP over IPv6
Enhanced LAN Base	Additional features
Industrial management	Layer 2 switching with 1:1 static Network Address Translation (NAT)
IP Lite license	Additional features
IPv4 routing	RIP, OSPF, EIGRP, VRF Lite, PIM for L3 multicast routing including sparse (SM) and dense (DM) mode.
IPv6 Routing	IPv6 Static routing, OSPFv3
Security	FIPS 140-2
Embedded Event Manager	EEM feature enabled with IP Lite license
DNA Essentials	Additional features
Cisco DNA Center	Discovery, topology, inventory, software image management
Visibility	DNA assurance, Device 360
Day-zero network bring-up automation	Cisco Network Plug-and-Play application
bring up dutomation	

Want to Buy



Get a Quote

Why **Gntme.com**

As a leading network hardware supplier, gntme.com focuses on original new ICT equipment of Cisco,
Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.



Countries we Sold



Customers Trusted



Inventory Available



50%-98% Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +971 503823786 /+971 42409998
- Email:sales@gntme.com