

IE-2000-4TS-L Datasheet



Get a Quote

Overview

IE-2000-4TS-L is the IE2000 series 4 10/100 RJ45 ports, 2 FE SFP, and LAN Lite switch. The Cisco IE 2000 Series are designed for low cost, low ports, and small sizes. They offer:

1. Four, eight, or 16 10/100Base-T Ethernet ports (Small Form-Factor Pluggable [SFP] downlinks on selected models); fixed configurations with a compact form factor
2. Two gigabit combo ports: SFP (100 Mbps and 1 Gbps) or RJ45 uplink
3. Dual-input DC power supply, alarm relays, DIN rail mount
4. Industrial Power over Ethernet (PoE) solution
5. Conformal coating available
6. Swappable SD flash card and mini-USB connector
7. Industrial environmental compliance and certifications
8. Industrial partner applications: Ethernet/IP and PROFINET

Quick Spec

Table 1 shows the quick spec.

Part Number	IE-2000-4TS-L
Total Ports	6
RJ45 ports	4 FE
SFP ports	2 FE
Manufacturing license	LAN Lite
Dimensions (H x W x D) including DIN rail	5.1" H x 2.95" W x 4.51" D in (130mm H x 74.9mm W x 115mm D)
Weight	IE-2000 6 ports chassis: 2.45 lb (1.11 kg)

Supported Products

Table 2 shows the supported modules, cards, licenses and accessories.

Model	Description
SD-IE-1GB	1GB SD Memory Card
GLC-FE-100LX-RGD	Cisco GLC-FE-100LX-RGD 100Mbps Single Mode Rugged SFP
GLC-FE-100LX-RGD	Cisco GLC-FE-100LX-RGD 100Mbps Single Mode Rugged SFP
GLC-FE-100FX	100BASE-FX SFP for FE port
GLC-FE-100LX	100BASE-LX SFP for FE port
GLC-FE-100EX	100BASE-EX SFP (40km)
GLC-FE-100ZX	100BASE-ZX SFP (80km)
GLC-FE-100BX-D	100BASE-BX10-D SFP
GLC-FE-100BX-U	100BASE-BX10-U SFP

L-IE2000-L-B=	IE2000 LAN Lite to LAN Base e-license
LIC-IE2000-L-IP=	IE2000 LAN Lite to IPLite e-license
STK-RACK-DINRAIL=	19 in. DIN Rail mount kit

Compare to Similar Items

Table 3 shows the comparison.

Part Number	IE-2000-4TS-L	IE-2000-4T-L	IE-2000-4TS-G-L
Total Ports	6	6	6
RJ45 ports	4 FE	6 FE	4 FE
SFP ports	2 FE	-	2 GE
Manufacturing license	LAN Lite	LAN Lite	LAN Lite

Ordering Guide

 [\[PDF\] Cisco Industrial Ethernet Switches Ordering Guide](#)

 [\[PDF\] Simple Cisco Industrial Ethernet Switches \(IE 4000, IE 2000 included\) Selection Guides](#)

Get More Information

Do you have any question about the C9500-32QC-A?

Contact us now via [Live Chat](#) or sales@gntme.com

Specification

IE-2000-4TS-L Specification	
Physical Specification	
Total Ports	6
RJ45 ports	4 FE
SFP ports	2 FE
Manufacturing license	LAN Lite
Hardware	<ul style="list-style-type: none"> • 256 MB DRAM with ECC memory • IEEE 1588v2 FPGA • 64 MB on-board flash memory • 1GB removable SD flash memory card (optional) • Mini-USB connector
Alarm	<ul style="list-style-type: none"> • Alarm I/O: Two alarm inputs to detect dry contact open or close; one alarm output relay
Power consumption	<ul style="list-style-type: none"> • 4-port downlink models: 9.5-15 W
Connectors and cabling	<ul style="list-style-type: none"> • 10/100/1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling
Dimensions (H x W x D) including DIN rail	<ul style="list-style-type: none"> • IE-2000 6 ports (copper downlinks) chassis: 5.1"H x 2.95"W x 4.51"D in (130mm H x 74.9mm W x 115mm D)
Weight	<ul style="list-style-type: none"> • IE-2000 6 ports chassis: 2.45 lb (1.11 kg)

