IE-2000-8TC-G-B Datasheet





Overview

IE-2000-8TC-G-B is the IE2000 series 8 10/100, 2 T/SFP, and LAN Base switch. The Cisco IE 2000 Series are designed for low cost, low ports, and small sizes. They offer:

- 1.Four, eight, or 16 10/100Base-T Ethernet ports (Small Form-Factor Pluggable [SFP] downlinks on selected models); fixed configurations with a compact form factor
- 2. Two gigabit combo ports: SFP (100 Mbps and 1 Gbps) or RJ45 uplink
- 3. Dual-input DC power supply, alarm relays, DIN rail mount
- 4. Industrial Power over Ethernet (PoE) solution
- 5. Conformal coating available
- 6. Swappable SD flash card and mini-USB connector
- 7. Industrial environmental compliance and certifications
- 8. Industrial partner applications: Ethernet/IP and PROFINET

Quick Spec

Table 1 shows the quick spec.

Part Number	IE-2000-8TC-G-B
Total Ports	10
RJ45 Ports	8 FE
Combo Ports	2 GE
Manufacturing license	LAN Base

Product Details

Figure 1 shows the front view of IE2000 8TC-G switches.



(1)	8 10/100
(2)	2 T/SFP
(3)	SD Flash
(4)	2 Dry-contact alarm inputs, and 1 alarm relay output
(5)	Dual DC inputs
(6)	Console port RJ45 and Mini USB

Supported Products

Table 2 shows the supported modules, cards, licenses and accessories.

Model	Description
SD-IE-1GB	1GB SD Memory Card
GLC-SX-MM-RGD	Cisco GLC-SX-MM-RGD 1000Mbps Multi-Mode Rugged SFP
GLC-BX40-U-I	1000BASE-BX10 SFP module for single-strand SMF, 1310-nm TX/1550-nm RX wavelength, single LC/PC connector
GLC-TE	1000BASE-T SFP transceiver module for Category 5 copper wire
GLC-ZX-SM	1000BASE-ZX SFP
GLC-BX-U	1000BASE-BX SFP, 1310NM
SFP-GE-L	1000BASE-LX/LH SFP (DOM)
GLC-ZX-SMD	Cisco GLC-ZX-SMD 1000BASE-ZX SFP transceiver module, SMF, 1550nm, DOM
GLC-SX-MMD	Cisco GLC-SX-MMD 1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
LIC-IE2000-IP-L=	IE2000 LAN Base or Enhanced LAN Base to IPLite e-license
L-IE2000-B-E=	IE2000 LAN Base to Enhanced LAN Base e-license
STK-RACK-DINRAIL=	19 in. DIN Rail mount kit

Compare to Similar Items

Table 3 shows the comparison.

Part Number	IE-2000-8TC-G-L	IE-2000-8TC-G-B
Total Ports	10	10
RJ45 ports	8 FE	8 FE
Combo Ports	2 GE	2 GE
Manufacturing license	LAN Lite	LAN Base

Ordering Guide



[PDF] Simple Cisco Industrial Ethernet Switches (IE 4000, IE 2000 included) Selection Guides

Get More Information

Do you have any question about the C9500-32QC-A?

Contact us now via **Live Chat** or sales@gntme.com

IE-2000-8TC-G-B Specification		
Physical Specification		
Total Ports	10	
RJ45 Ports	8 FE	
Combo Ports	2 GE	
Manufacturing license	LAN Base	
Power consumption	8-port downlink models: 12.5-20 W	
Hardware	 256 MB DRAM with ECC memory IEEE 1588v2 FPGA 64 MB on-board flash memory 1GB removable SD flash memory card (optional) Mini-USB connector 	
Alarm	Alarm I/O: Two alarm inputs to detect dry contact open or close; one alarm output relay	
Connectors and cabling	• 10/100/1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling	
IE2000 Software Features		
LAN Lite license	Baseline features	
Layer 2 switching	IEEE 802.1, 802.3, 802.3at, 802.3af standard (see Table 8), VTPv2, NTP, UDLD, CDP, LLDP, Unicast MAC filter, Resilient Ethernet Protocol (REP), Media Redundancy Protocol (MRP) Ring (IEC 62439-2)	
Security	SCP, SSH, SNMPv3, TACACS+, RADIUS Server/Client, MAC Address Notification, BPDU Guard, SPAN session	
Multicast	IGMPv1, v2, v3 Snooping, IGMP filtering, IGMP Querier	
Management	Fast Boot, Express Setup, Web Device Manager, CNA, Cisco Prime, LMS, MIB, SmartPort, SNMP, syslog	
Industrial Ethernet	EtherNet/IP, Profinet v2	
LAN Base license	Additional features	
Layer 2 switching	VTPv3, EtherChannel, Voice VLAN, Flexlink	
Security	IPv4 Port-Security, DHCP Snooping, Dynamic ARP Inspection, IP Source Guard, 802.1x, Guest VLAN. MAC Authentication Bypass, 802.1x Multi-Domain Authentication, Storm Control, Trust Boundary, Access-List (ACL)	
Quality of service	IPv4 Ingress Policing, Rate-Limit, Egress Queuing/Shaping, AutoQoS, PROFINET QoS	
Management	Port-Based DHCP, Storm Control - Unicast, Multicast, Broadcast, SPAN Sessions, RSPAN, DHCP Server, Customized TCAM/SDM Size Configuration, Embedded Event Manager (EEM)	
Industrial Ethernet	IEEE 1588 PTPv2	
IPv4 routing	IPv4 static routing	
IPv6 routing	IPv6 host support, HTTP over IPv6, SNMP over IPv6	
Enhanced LAN Base	Additional features	
Industrial management	Layer 2 switching with 1:1 static Network Address Translation (NAT)	

IP Lite license	Additional features
IPv4 routing	RIP, OSPF, EIGRP, VRF Lite, PIM for L3 multicast routing including sparse (SM) and dense (DM) mode.
IPv6 Routing	IPv6 Static routing, OSPFv3
Security	FIPS 140-2
Embedded Event Manager	EEM feature enabled with IP Lite license
DNA Essentials	Additional features
Cisco DNA Center	Discovery, topology, inventory, software image management
Visibility	DNA assurance, Device 360
Day-zero network bring-up automation	Cisco Network Plug-and-Play application

Want to Buy

Order Now

Get a Quote

Why **Gntme.com**

As a leading network hardware supplier, gntme.com focuses on original new ICT equipment of Cisco,
Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.



Countries we Sold



18,000+
Customers Trusted



\$20,000,000 Inventory Available



Off Global List Price



Safe Online Shopping

Contact Us

- Tel: +971 503823786 /+971 42409998
- Email: sales@gntme.com