

# N9K-C93108TC-FX Datasheet



[Get a Quote](#)

## Overview

The Cisco N9K-C93108TC-FX Switch is a 1RU switch that supports 2.16 Tbps of bandwidth and over 1.25bps. The 48 10GBASE-T downlink ports on the 93108TC-FX can be configured to work as 100-Mbps, 1-Gbps, or 10-Gbps ports. The uplink can support up to six 40- and 100-Gbps ports, or a combination of 1-, 10-, 25-, 40, 50-, and 100-Gbps connectivity, offering flexible migration options.

## Quick Specs

Table 1 shows the Specs.

SKU	N9K-C93108TC-FX
CPU	4 cores
System memory	24 GB
SSD drive	128 GB
System buffer	40 MB
Management ports	2 ports: 1 RJ-45 and 1 SFP+
USB ports	1
RS-232 serial ports	1
Power supplies (up to 2)	500W AC, 930W DC, or 1200W HVAC/HVDC
RS-232 serial ports	1

## Product Details

Cisco N9K-C93108TC-FX provides the following features:

- (1)Architectural Flexibility
- (2)Architectural Flexibility
- (3)High Scalability, Flexibility, and Security
- (4)Intelligent Buffer Management
- (5)RDME over Converged Ethernet – RoCE Support
- (6)LAN and SAN Convergence
- (7)Hardware and Software High Availability
- (8)Purpose-Built Cisco NX-OS Software Operating System with Comprehensive, Proven Innovations
- (9)Cisco Tetration Analytics Platform Support
- (10)Cisco Network Assurance Engine (NAE)

## Compare to Similar Items

Table 2 shows the comparison.

Product Name	N9K-C93108TC-FX	N9K-C93180YC-FX	N9K-C9348GC-FXP
Ports	48 x 100M/1/10GBASE-T and 6 x 40/100-Gbps QSFP28 ports	48 x 1/10/25-Gbps and 6 x 40/100- Gbps QSFP28 ports	48 x 1-GBASE-T ports, 4 x 1/10/25-Gbps SFP28 ports and 2 x 40/100 QSFP28 ports
CPU	4 cores	6 cores	4 cores
System memory	24 GB	Up to 32 GB	24 GB

SSD drive	128 GB	128 GB	128 GB
System buffer	40 MB	40 MB	40 MB
USB ports	1	1	1
RS-232 serial ports	1	1	1

**Get More Information**  
Do you have any question about the Cisco C9410R?  
Contact us now via [Live Chat](#) or [sales@gntme.com](mailto:sales@gntme.com)

## Specification

N9K-C93108TC-FX Specification	
Hardware performance and scalability	
Ports	48 x 100M/1/10GBASE-T and 6 x 40/100-Gbps QSFP28 ports
Downlink supported speeds	100-Mbps and 1/10-Gbps speeds
CPU	4 cores
System memory	24 GB
SSD drive	128 GB
System buffer	40 MB
Management ports	2 ports: 1 RJ-45 and 1 SFP+
USB ports	1
RS-232 serial ports	1
Power supplies (up to 2)	500W AC, 930W DC, or 1200W HVAC/HVDC
Typical power (AC/DC)	276W
Maximum power (AC/DC)	460W
Input voltage (AC)	100 to 240V
Input voltage (High-Voltage AC [HVAC])	200 to 277V
Input voltage (DC)	-48 to -60V
Input voltage (High-Voltage DC [HVDC])	-240 to -380V
Frequency (AC)	50 to 60 Hz
Fans	4
Airflow	Port-side intake and exhaust
Physical dimensions (H x W x D)	1.72 x 17.3 x 22.5 in. (4.4 x 43.9 x 57.1 cm)
Acoustics	64.2 dBA at 40% fan speed, 68.9 dBA at 70% fan speed, and 77.8 dBA at 100% fan speed

RoHS compliance	Yes
MTBF	319,790 hours
Environmental properties	
Operating temperature	32 to 104°F (0 to 40°C)
Nonoperating (storage) temperature	-40 to 158°F (-40 to 70°C)
Humidity	5 to 95% (noncondensing)
Altitude	0 to 13,123 ft (0 to 4000m)

## Download Resource

---

### Transition Guide

 [Select and Upgrade Cisco Data Center Switch](#)

## Want to Buy

---


[Order Now](#)


[Get a Quote](#)


## Why [Gntme.com](#)


---


As a leading network hardware supplier, [gntme.com](#) focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.

  
200+  
Countries we Sold

  
18,000+  
Customers Trusted

  
\$20,000,000  
Inventory Available

  
50%-98%  
Off Global List Price

  
100%  
Safe Online Shopping

## Contact Us

---

- Tel: +971 503823786 / +971 42409998
- Email: [sales@gntme.com](mailto:sales@gntme.com)