

N9K-C93120TX Datasheet



[Get a Quote](#)

Overview

N9K-C93120TX is the Nexus 9300 with 96p 100M/1/10G-T and 6p 40G QSFP. The Cisco Nexus 9300 platform consists of fixed-port switches designed for top-of-rack (ToR) and middle-of-row (MoR) deployment in data centers that support enterprise applications, service provider hosting, and cloud computing environments. They are Layer 2 and 3 nonblocking 10 and 40 Gigabit Ethernet switches with up to 2.56 terabits per second (Tbps) of internal bandwidth.

Quick Specs

Table 1 shows the Quick Specs.

Product Code	N9K-C93120TX
Ports	96 fixed 1/10GBASE-T and 6 QSFP+ ports
Supported speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
40 Gigabit Ethernet uplink ports	6 fixed QSFP+ ports
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)
Weight	26 lb (11.8 kg) (without power supplies, fans, or uplink module)

Product Details

Table 2 shows Cisco Nexus 9300 Platform Switch Features.

Feature	Benefit
Predictable high performance	Latency of 1 to 2 microseconds with up to 1.28 Tbps of bandwidth enables customers to build a robust switch fabric scaling from as few as 200 10-Gbps server ports to more than 200,000 10-Gbps server ports.
Increased integrated buffer space	Up to a total of 50 MB of integrated shared buffer space allows better management of speed mismatch between access and uplink ports.
Designed for availability	Hot-swappable, redundant power supplies and fan trays increase availability.
Flexible airflow configuration	Port-side intake and port-side exhaust airflow configurations are both supported.
CPU, SSD, and memory	Dual-core 2.5-GHz x86 CPUs with 64-GB SSD drive and 16 GB of memory provide enhanced network performance.
Power efficiency	All Cisco Nexus 9000 Series power supplies are 80 Plus Platinum rated.
Advanced optics	Cisco offers a pluggable 40 Gigabit Ethernet QSFP+ transceiver that enables customers to use existing 10 Gigabit Ethernet data center cabling to support 40 Gigabit Ethernet connectivity. This technology facilitates adoption of 40 Gigabit Ethernet with no cable infrastructure upgrade cost.

The Accessories

Table 3 shows the supported accessories.

Model	Description
N9K-M6PQ-E	Uplink Module for Nexus 9300, 6p 40G QSFP

N9K-M6PQ	Uplink Module for Nexus 9300, 6p 40G QSFP
N9K-M12PQ	Uplink Module for Nexus 9300, 12p 40G QSFP
N9K-M4PC-CFP2	Uplink Module for Nexus 9300, 4p 100G
UCSC-PSU-930WDC	Nexus 9000 930W DC PS, Port-side Intake
UCS-PSU-6332-DC	Nexus 9000 930W DC PS, Port-side Exhaust
N9K-PUV-1200W	Nexus 9300 1200W Universal Power Supply, Bi-directional air flow and Supports AC/HVDC
N9K-C9300-FAN2	Nexus 93128 & 9396 Fan 2, Port-side Intake
N9K-C9300-FAN2-B	Nexus 93128 & 9396 Fan 2, Port-side Exhaust
NXA-FAN-30CFM-F	Nexus 2K/3K/9K Single Fan for 1RU switch, port side exhaust airflow
NXA-FAN-30CFM-B	Nexus 2K/3K/9K Single Fan for 1RU switch, port side intake airflow
N93-LAN1K9=	Enhanced L3 including full OSPF, EIGRP, BGP for Nexus 9200/9300 Platform

Compare to Similar Items

Table 4 shows the comparison.

Product Code	N9K-C93120TX	
Ports	96 fixed 1/10GBASE-T and 6 QSFP+ ports	96 fixed 1/10GBASE-T ports
Supported speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)	5.3 x 17.5 x 22.5 in. (13.3 x 44.5 x 57.1 cm)
Weight	26 lb (11.8 kg) (without power supplies, fans, or uplink module)	32.56 lb (14.8 kg) (without power supplies, fans, or uplink module)

Get More Information

Do you have any question about the Cisco N9K-C93120TX?Contact us

now via [Live Chat](#) or sales@gntme.com

Specification

N9K-C93120TX Specification	
Ports	96 fixed 1/10GBASE-T and 6 QSFP+ ports
Supported speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
40 Gigabit Ethernet uplink ports	6 fixed QSFP+ ports
	Advanced QSFP+ optics enable connectivity using existing 10 Gigabit Ethernet fiber. The switch offers 25 MB of additional packet buffer space shared with all ports for more resilient operations.
Power supplies (up to 2)	1200W AC, 930W DC, or 1200W HVAC/HVDC
Typical power (AC)	542W
Maximum power (AC)	948W
Input voltage (AC)	100 to 240V *PSU redundancy is not supported when used in 110V

Input voltage (HVAC)	200 to 277V
Input voltage (DC)	-40V to -72V DC (min-max) -48V to -60V DC (nominal)
Input voltage (HVDC)	-240 to -380V
Frequency (AC)	50 to 60 Hz
Fans	2
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)
RoHS compliance	Yes
Weight	26 lb (11.8 kg) (without power supplies, fans, or uplink module)

Download Resource

Support and Resources

 [Cisco Nexus 9300 Switches Datasheet](#)

Transition Guide

 [Select and Upgrade Cisco Data Center Switch](#)


Want to Buy


[Order Now](#)


[Get a Quote](#)


Why [Gntme.com](#)


As a leading network hardware supplier, [gntme.com](#) focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.


200+
Countries we Sold


18,000+
Customers Trusted


\$20,000,000
Inventory Available


50%-98%
Off Global List Price


100%
Safe Online Shopping

Contact Us

- Tel: +971 503823786 / +971 42409998
- Email: sales@gntme.com