

WS-C2960L-24TQ-LL

Datasheet

[Get a Quote](#)



Overview

WS-C2960L-24TQ-LL offering 24 x GigE ports, 4 x 10G SFP and LAN Lite, is one of the Cisco Catalyst 2960-L Series Switches. These 2960-L switches are fixed-configuration, Gigabit Ethernet switches that provide entry-level enterprise-class Layer 2 access for branch offices, conventional workspaces, and out-of-wiring closet applications. Designed for operational simplicity to lower total cost of ownership, they enable secure and energy-efficient business operations with a range of Cisco IOS Software features.

Quick Specs

Figure 1 shows the appearance of WS-C2960L-24TQ-LL.



Table 1 shows the Quick Specs.

Product Code	WS-C2960L-24TQ-LL
IOS	LAN Lite
Forwarding bandwidth	64 Gbps
Switching bandwidth	128 Gbps
10/100/1000 Ethernet Ports	24
Uplink Interfaces	4 x 10G SFP
Fanless	Y
DRAM	512 MB
Flash memory	256 MB
Dimensions (H x D x W)	1.73 x 9.45 x 17.5 in. (4.4 x 24 x 44.5 cm)
Net Weight	6.06 lb (2.75 kg)

Product Details

Figure 2 shows the front panel.



Note:

(1)	Mode button
(2)	USB mini-Type B (console) port
(3)	USB Type A port and RJ-45 Console Port
(4)	24 x 10/100/1000 ports
(5)	SFP module slots

· There are a Security slot and an AC power connector on the back panel.

The Accessories

Table 2 shows the recommended elements for the WS-C2960L-24TQ-LL.

Model	Description
CAB-CONSOLE-USB	Cisco CAB-CONSOLE-USB Console Cable 6 ft with USB Type A and mini-B
CAB-CONSOLE-RJ45	Cisco CAB-CONSOLE-RJ45 Console Cable 6ft with RJ45 and DB9F
CAB-ACE=	CAB-ACE= AC Power Cord (Europe), C13, CEE 7, 1.5M
CAB-ACU=	CAB-ACU= AC Power Cord (UK), C13, BS 1363, 2.5m

Compare to Similar Items

Table 3 shows the comparison of WS-C2960L-24TS-LL and WS-C2960L-24TQ-LL.

Model	WS-C2960L-24TS-LL	WS-C2960L-24TQ-LL
IOS	LAN Lite	LAN Lite
Forwarding bandwidth	28 Gbps	64Gbps
Switching bandwidth	56 Gbps	128 Gbps
10/100/1000 Ethernet Ports	24	24
Uplink Interfaces	4 x 1G SFP	4 x 10G SFP

Get more information

Do you have any question about the Cisco C9410R?

Contact us now via [Live Chat](#) or sales@gntme.com

Specification

WS-C2960L-24TQ-LL Specification	
Configurations	
10/100/1000 Ethernet Ports	24
Uplink Interfaces	4 SFP
Available PoE Power	-
Fanless	Y
Dimensions (H x D x W)	1.73 x 9.45 x 17.5 in. (4.4 x 24 x 44.5 cm)
Net Weight	6.06 lb (2.75 kg)
Console Ports	
RJ45 Ethernet	1
USB mini-B	1
USB-A port for storage and Bluetooth console	1
Memory and Processor	
CPU	ARMv7 800 MHz
DRAM	512 MB
Flash memory	256 MB
Performance	
Forwarding bandwidth	64 Gbps
Switching bandwidth	128 Gbps
Forwarding rate (64-byte L3 packets)	41.67 Mpps
Unicast MAC addresses	8K
Maximum active VLANs	64
VLAN IDs available	4094
Maximum STP instances	64
Maximum SPAN sessions	1
MTU-L3 packet	9198 bytes
Jumbo Ethernet frame	10,240 bytes
MTBF in hours (Data)	2,412,947
MTBF in hours (PoE)	909,838
Environment	
Operating temperature	
Up to 5,000 ft	23°F to 113°F (−5°C to 45°C)

Up to 10,000 ft	23°F to 104°F (–5°C to 40°C)
Operating altitude	10,000 ft (3000m)
Operating relative humidity	5% to 90% at 40°C
Storage temperature	–13° to 158°F (–25° to 70°C)
Storage altitude	15,000 ft (4500m)
Storage relative humidity	5% to 95% at 65°C
Storage altitude	Minimum ambient temperature for cold start is 0°C (32°F)
Electrical	Data
Voltage (autoranging)	110 to 220V AC in
Frequency	50 to 60 Hz
Current	0.20A to 0.33A
Power rating (maximum consumption)	0.06 kVA
Power consumption (watts) 0% traffic 10% traffic 100% traffic Weighted average	19.4 26.5 26.5 24.1
Safety and Compliance	
Safety	UL 60950-1 Second Edition, CAN/CSA-C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, AS/NZS 60950-1
EMC: emissions	47CFR Part 15 (CFR 47) Class A, AS/NZS CISPR22 Class A, CISPR22 Class A, EN55022 Class A, ICES003 Class A, VCCI Class A, EN61000-3-2, EN61000-3-3, KN22 Class A, CNS13438 Class A
EMC: immunity	EN55024, CISPR24, EN300386, KN24
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU
Telco	Common Language Equipment Identifier (CLEI) code
U.S. government certifications	USGv6 and IPv6 Ready Logo
Connectors and Interfaces	
Ethernet interfaces	10BASE-T ports: RJ-45 connectors, 2-pair Category 3, 4, or 5 unshielded twisted-pair (UTP) cabling
	100BASE-TX ports: RJ-45 connectors, 2-pair Category 5 UTP cabling
	1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling
	1000BASE-T SFP-based ports: RJ-45 connectors, 4-pair Category 5 UTP cabling
Indicator LEDs	Per-port status: link integrity, disabled, activity, speed, and full duplex
	System status: system, PoE, and link speed
Console cables	CAB-CONSOLE-RJ45 Console cable 6 ft. with RJ-45
	CAB-CONSOLE-USB Console cable 6 ft. with USB Type A and mini-B connectors
Power	Use the supplied AC power cord to connect the AC power connector to an AC power outlet

Download Resource

Selection Decision

 [Cisco's New Switch Selection Decision 2018](#)

Support and Resources

 [Cisco Catalyst 2960-L Series Switch Datasheet](#)

Transition Guide

 [Cisco Catalyst 2960/2960-SF/2960-S Series Transition](#)

 [Guide Guide to Upgrade Cisco Access and Backbone Switch](#)

 [Selecting Cisco Switches-Campus, Branch, Digital Building](#)

Want to Buy

[Order Now](#)

[Get a Quote](#)

Why [Gntme.com](#)

As a leading network hardware supplier, [gntme.com](#) focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +971 503823786 / +971 42409998
- Email: sales@gntme.com