

WS-C3650-12X48UZ-S Datasheet



[Get a Quote](#)

Overview

Stackable 12 100M/1G/2.5G/5G/10G Cisco UPOE™ downlink ports, 36 10/100/1000 Cisco UPOE™ downlink ports, two 40-Gigabit uplink QSFP+ ports, 1100-W power supply

Specification

WS-C3650-12X48UZ-S Specification

General

Device Type	Switch - 48 ports - L3 - managed - stackable
Enclosure Type	Desktop, rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	36 x 10/100/1000 (UPOE) + 12 x 100/1000/2.5G/5G/10G (UPOE) + 2 x 40 Gigabit QSFP+ (uplink)
Power Over Ethernet (PoE)	UPOE
PoE Budget	660 W
Performance	Switching capacity: 272 Gbps Forwarding performance: 202.38 Mpps Stacking bandwidth: 160 Gbps
Capacity	IPv4 routes: 24000 NetFlow entries: 24000 Virtual interfaces (VLANs): 4094 Switched virtual interfaces (SVIs): 1000 IPv4 routes: 24000
MAC Address Table Size	32000 entries
Jumbo Frame Support	9198 bytes
Routing Protocol	BGP-4, IS-IS, RIP-1, RIP-2, PIM-SM, static IP routing, PIM-DM, EIGRP for IPv6, OSPFv3, PIM-SSM, policy-based routing (PBR), RIPng
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, SSH, CLI
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features	Full duplex capability, layer 2 switching, DHCP support, auto-negotiation, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, IPv6 support, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS), RADIUS support, Virtual Route Forwarding-Lite (VRF-Lite), MLD snooping, Dynamic ARP Inspection (DAI), Cisco StackWise Technology, Unicast Reverse Path Forwarding (URPF), Uni-Directional Link Detection (UDLD), Rapid Per-VLAN Spanning Tree Plus (PVRST+), Shaped Round Robin (SRR), LLDP support, Link Aggregation Control Protocol (LACP), MAC Address Notification, Remote Switch Port Analyzer (RSPAN), Hot Standby Router Protocol (HSRP) support, Energy Efficient Ethernet, Strict Priority Queuing (SPQ), Class of Service (CoS), Flexible NetFlow (FNF), DiffServ Code Point (DSCP) support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at

WS-C3650-12X48UZ-S Specification

RAM	4 GB
Flash Memory	4 GB
Status Indicators	Port transmission speed, port duplex mode, system, active, status, PoE
Expansion / Connectivity	
Interfaces	36 x 1000Base-T RJ-45 UPOE - 60 W 1 x USB Type A 1 x serial (console) RJ-45 management 1 x management (Gigabit LAN) RJ-45 management 1 x management (mini-USB) Type B management 12 x 100/1000/2.5G/5G/10GBase-T RJ-45 UPOE - 60 W 4 x 40Gbit WAN QSFP+ uplink
Expansion Slots	1 (total) / 1 (free) x Stacking Module slot
Power	
Power Device	Internal power supply - hot-plug
Installed Qty	1 (installed) / 2 (max)
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Power Provided	1100 Watt
Voltage Required	AC 120/230 V (50/60 Hz)
Miscellaneous	
Rack Mounting Kit	Included
MTBF	203,130 hours
Compliant Standards	CISPR 22 Class A, GOST, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, NOM, EN 61000-3-3, EN55024, EN55022 Class A, ICES-003 Class A, RoHS, UL 60950-1 Second Edition, KCC, FCC Part 15 A, ISO 7779, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, VCCI Class A, KN24, KN22 Class A
Software / System Requirements	
Software Included	Cisco IOS IP Base
Dimensions & Weight	
Width	17.5 in
Depth	19.1 in
Height	1.7 in
Weight	17.64 lbs
Manufacturer Warranty	
Service & Support	Limited warranty - replacement - lifetime - response time: next business day Technical support - phone consulting - 90 days
Environmental Parameters	

WS-C3650-12X48UZ-S Specification

Min Operating Temperature	23 °F
Max Operating Temperature	113 °F
Humidity Range Operating	5 - 96% (non-condensing)
Min Storage Temperature	-40 °F
Max Storage Temperature	158 °F

Download Resource

Selection Decision

 [Cisco's New Switch Selection Decision 2018](#)

Support and Resources

 [Cisco Switch Catalyst 3650 Series Datasheet](#)

Transition Guide

 [Find the Right 3650 and 3850 Models](#)

 [Guide to Upgrade Cisco Access and Backbone Switch](#)

 [Selecting Cisco Switches-Campus, Branch, Digital Building](#)

Want to Buy

[Order Now](#)

[Get a Quote](#)

Why [Gntme.com](#)

As a leading network hardware supplier, [gntme.com](#) focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +971 503823786 / +971 42409998
- Email: sales@gntme.com

