

WS-C3650-24PDM-L Datasheet

Get a Quote



Overview

Stackable 24 10/100/1000 PoE+ downlink ports, two 1-Gigabit SFP uplink ports and two 10-Gigabit SFP+ uplink ports, Fixed 640-W power supply

Specification

| WS-C3650-24PDM-L Specification | |
|---------------------------------------|----------------------------|
| Capacity | |
| Type | Virtual interfaces (VLANs) |
| Value | 255 |
| Dimensions & Weight | |
| Width | 17.5 in |
| Depth | 11.7 in |
| Height | 1.7 in |
| Weight | 12.26 lbs |
| Environmental Parameters | |
| Min Operating Temperature | 23 °F |
| Max Operating Temperature | 113 °F |
| Humidity Range Operating | 5 - 96% (non-condensing) |
| Min Storage Temperature | -40 °F |
| Max Storage Temperature | 158 °F |
| Flash Memory | |
| Installed Size | 2 GB |
| Header | |
| Compatibility | PC |
| Manufacturer | Cisco Systems |
| Packaged Quantity | 1 |
| Product Line | Cisco Catalyst |
| Model | 3650-24PDM-L |

WS-C3650-24PDM-L Specification

| | |
|----------------------------|--|
| Brand | Cisco |
| Interface Provided | |
| Qty | 24 |
| Type | Management (mini-USB) |
| Connector Type | Type B |
| Comments | Management |
| PoE Power | 30 W |
| Miscellaneous | |
| Rack Mounting Kit | Included |
| Compliant Standards | BSMI CNS 13438 Class A, CISPR 22 Class A, CISPR 24, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, EN 61000-3-2, EN 61000-3-3, EN55022 Class A, EN55024, FCC Part 15 A, GOST, ICES-003 Class A, IEC 60950-1 Second Edition, ISO 7779, KCC, KN22 Class A, KN24, NOM, RoHS, UL 60950-1 Second Edition, VCCI Class A |
| Authentication Method | Kerberos, RADIUS, Secure Shell (SSH), TACACS+ |
| MTBF | 528,280 hours |
| Height (Rack Units) | 1 |
| Color Category | Black |
| Networking | |
| Type | Switch |
| Connectivity Technology | Wired/Wireless |
| Remote Management Protocol | CLI, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 1, SNMP 2c, SNMP 3, SSH, Telnet |
| Compliant Standards | IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z |
| Status Indicators | Active, PoE, Port duplex mode, Port transmission speed, Status, System |
| Ports Qty | 24 |
| Features | Access Control List (ACL) support, ARP support, Auto-negotiation, Auto-uplink (auto MDI/MDI-X), Class of Service (CoS), DHCP snooping, DHCP support, DiffServ Code Point (DSCP) support, Dynamic ARP Inspection (DAI), Dynamic Trunking Protocol (DTP) support, Energy Efficient Ethernet, Full duplex capability, Hot Standby Router Protocol (HSRP) support, IGMP snooping, IPv6 support, Layer 2 switching, Link Aggregation Control Protocol (LACP), LLDP support, MAC Address Notification, MLD snooping, Multiple Spanning Tree Protocol (MSTP) support, Port Aggregation Protocol (PAgP) support, Quality of Service (QoS), RADIUS support, Rapid Per-VLAN Spanning Tree Plus (PVRST+), Rapid Spanning Tree Protocol (RSTP) support, Remote Switch Port Analyzer (RSPAN), Shaped Round Robin (SRR), Spanning Tree Protocol (STP) support, Strict Priority Queuing (SPQ), Syslog support, Trivial File Transfer Protocol (TFTP) support, Trunking, Uni-Directional Link Detection (UDLD), Unicast Reverse Path Forwarding (URPF), VLAN support |
| Routing Protocol | Static IP routing |

WS-C3650-24PDM-L Specification

| | |
|---------------------------|----------------------------------|
| MAC Address Table Size | 32000 entries |
| Stackable | Stackable |
| Subcategory | Network hubs and switches |
| Power Over Ethernet (PoE) | PoE+ |
| Manageable | Yes |
| Form Factor | Desktop, Rack-mountable |
| Jumbo Frame Support | 9198 bytes |
| Subtype | Gigabit Ethernet |
| PoE Budget | 390 W |
| Performance | |
| Type | Switching capacity |
| Value | 88 Gbps |
| Ports | |
| Qty | 24 |
| Type | 10/100/1000 (PoE+) |
| Ports (2nd) | |
| Qty | 2 |
| Type | 10 Gigabit SFP+ |
| Power Device | |
| Frequency Required | 50/60 Hz |
| Power Provided | 640 Watt |
| Installed Qty | 1 |
| Max Supported Qty | 2 |
| Nominal Voltage | AC 120/230 V |
| Power Redundancy | Optional |
| Power Redundancy Scheme | 1+1 (with optional power supply) |
| Type | Internal power supply |
| Hot-Plug | Hot-plug |
| RAM | |

| WS-C3650-24PDM-L Specification | |
|---------------------------------------|---------------------------|
| Installed Size | 4 GB |
| Service | |
| Support Details Type | Technical support |
| Support Details Service Included | Phone consulting |
| Support Details Full Contract Period | 90 days |
| Service & Support | |
| Type | Limited lifetime warranty |
| Service & Support Details | |
| Response Time | Next business day |
| Slot Provided | |
| Type | Stacking Module slot |
| Total Qty | 1 |
| Free Qty | 1 |
| Software | |
| Type | Cisco IOS LAN Base |

Download Resource

Selection Decision

 [Cisco's New Switch Selection Decision 2018](#)

Support and Resources

 [Cisco Switch Catalyst 3650 Series Datasheet](#)

Transition Guide

 [Guide to Upgrade Cisco Access and Backbone Switch](#)

 [Selecting Cisco Switches-Campus, Branch, Digital Building](#)

Want to Buy

[Order Now](#)

[Get a Quote](#)

Why [Gntme.com](#)

As a leading network hardware supplier, gntme.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: [+971 503823786](tel:+971503823786) / [+971 42409998](tel:+97142409998)
- Email: sales@gntme.com